P5X16E024UL

SHUNT TRIP RELEASE FOR P5ME UL CERTIFIED, 24VAC/DC



Product designation	Shunt trip
Product type designation	P5X16E024UL
Description	Shunt trip releases for UL certified MCCBs.
Accessories for	Accessories for UL-compliant MCCBs

Operational characteristics			
Rated supply voltage AC		VAC	24
Rated supply voltage DC		VDC	24
Rated frequency		Hz	45…65
In-rush consumption		VA	0.58
Operating voltage		US	70…110
Average opening time		ms	50

Mechanical features			
Tightening torque for terminals			
	min	Nm	0.8
	max	Nm	1
	min	lbin	7
	max	lbin	9
Conductor section			
AWG/Kcmil			
	min		20
	max		16
Flexible w/o lug conductor section			
	min	mm²	0.5
	max	mm²	1.5
Flexible c/w lug conductor section			
	min	mm²	0.5
	max	mm²	1.5
Terminals			
	type		Screw
	tool		PZ2
Weight		g	50

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



Wiring diagrams

Certifications and compliance

Certificates

cULus

ETIM classification

EC000066 - Power contactor, AC switching

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding