FLEXIMARK® Character holder NM for assembly of characters made of acid-proof stainless steel for cable and component marking in the electrical industry



RoHS

Suitable for outdoor use

Cold-resistant

Corrosion-resistant

Acid-resistant

UV-resistant

Info
PR 10 NM 7 contained in FLEXIMARK® sample bag(article number M3251010)

Application range
Cable and component marking system
For outdoor applications

Benefits
For mounting MR stainless steel characters
Mounted with cable ties (maximum 7.9 mm width) or screws (up to 3 mm Ø)
Acid-resistant

Product features
Holder for up to 46 characters

Remark
Photographs are not to scale and do not represent detailed images of the respective products.
Contents: roll, metre, unit, marker, label

Technical Data

Info:	Height: approx. 11 mm Screw hole Ø: 3 mm
Material:	Acid resistant stainless steel AISI 316-V4a
Temperature range:	-80°C to +500°C

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.

Part number	Article designation	Length (mm)	Characters/unit
83254214	FLEXIMARK® PR10 NM4	48,8	4
83254213	FLEXIMARK® PR10 NM5	60,4	8
83254212	FLEXIMARK® PR10 NM7	83,1	12
83254211	FLEXIMARK® PR10 NM9	109	16
83254210	FLEXIMARK® PR10 NM24	286	46

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.