Chemical protection

ULTRANITRIL 377

Prolonged contact (or immersion) | continous wear

Comfort and reinforced mechanical resistance for long-lasting chemical protection



CHEMICAL PROTECTION
TYPE A

EN388	EN ISO 374-1	EN407
4122X	TYPE A AJKOPT	X1XXXX

CATEGORY 3

DEXTERITY
EN ISO 21420: 5/5

CE
0334

SPECIFIC ADVANTAGES

Cut protection

- A long cuff for a better protection of the forearm

Comfort

- Suitable for long-term wear; comfortable textile support, seamless working surfaces

Durability

- Optimised service life: high resistance to abrasion

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Chemical product blending
- Cleaning tanks
- Handling and transporting drums of chemical products
- Manipulating valves
- Manufacture and application of paints and varnishes
- Unloading fuel
- Heavy-duty packaging
- Industrial cleaning
- Print-press cleaning
- Automotive assembly

Edit 16/12/2024

Chemical protection

ULTRANITRIL 377

Prolonged contact (or immersion) | continous wear

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	1	2	2	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1 — CHEMICAL RISKS



TYPE A

A: Methanol
J: n-Heptane
K: Sodium hydroxide 40%
O: Ammonia 25%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Smooth
Material	Nitrile
Cuff characteristic	Feston Cuff
Colour.s	Green
Length (cm)	38
Thickness (mm)	1.35
European sizes	8 9 10

LOGISTIC DETAILS

Packaging	1 pair/bag 5 pairs/box 50 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/02/19/0480
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 16/12/2024