
Inductive sensor

BES M12MG-USC30B-BV03
BES004U

BALLUFF
sensors worldwide



- **Non-polarized**
- **Normally open (NO)**
- **3.00 mm**
- **Flush (shielded)**
- **Cable, PVC, 3.00 m**

General attributes

Approvals / Conformity	cULus
	CE
	EAC
Basic standard	IEC 60947-5-2
Enclosure Type per IEC 60529	IP67
Function indicator	Yes
Operating distance marking	■■
Polarity reversal protected	Yes
Power indicator	No
Short circuit protected	Yes
Trademark	GLOBAL
MTTF	315 a

Electrical attributes

Connection type	Cable
Eff. operating current Ie	100 mA
Eff. operating voltage Ue DC	24.0 V
Electrical version	DC, direct current
Load capacitance max. (at Ue)	1.000 µF
Minimum operating current Im	5 mA
Operating voltage UB max. DC [V]	36.0 V
Operating voltage UB min. DC [V]	10.0 V
Rated insulation voltage Ui	75 VDC
Rated short circuit current	100 A
Ripple max. (% of Ue)	15 %
Switching freq. f max. (at Ue)	1300 Hz
Switching function	Normally open (NO)
Switching output	Non-polarized
Voltage drop static max.	5.0 V

Mechanical attributes

Ambient temperature Ta max.	70 °C
Ambient temperature Ta min.	-25 °C
Assured operating distance Sa	2.40 mm
Cable diameter D max.	4.6 mm
Cable jacket material	PVC
Cable length	3.00 m
Conductor cross-section	0.34 mm²
Depth	43.0 mm
Diameter d1	M12x1
Eff. operating distance Sr	3.00 mm
Housing material	CuZn
Mech. installation condition	Flush (shielded)
Mounting length	40.0 mm
Number of conductors	2
Rated operating distance Sn [mm]	3.00 mm
Sensing face material	PA 12
Surface protection	Nickel-free coating
Tightening torque	15 Nm

Remarks
Specify maximum attainable switching frequency (not per IEC 60947-5-2)
The sensor is functional again after the overload has been eliminated.

For further information on MTTF/B10d, please refer to the MTTF / B10d Certificate.

Specification of the MTTF value and the B10d value do not represent any binding quality and/or life expectancy guarantees.

