Compact Power DistributorBSV 3 LS E/16 2 IP 44 1 m H07RN-F 5G1.5 3xCEE400 V + 3x230 V

For universal outdoor use and permanent use on sites, IP 44.





MADE IN GERMANY

Product number	1153680100
EAN	4007123654482

DESCRIPTION

- Splash-proof housing made of a special rubber compound for continuous use.
- Extremely robust, impact-resistant, resistant to ageing and weathering.
- Resistant to various oils, greases, petrol and acids, UV and ozone radiation.
- Temperature resistance of the housing -30 °C to +80 °C.
- Quality sockets in accordance with VDE 0620-2-1.
- Sturdy metal carrying handle.
- Oil-resistant rubber cable for permanent outdoor use.
- 3 protective contact sockets 230 V with self-closing lids.

TECHNICAL DATA

Cable quality	Rubber-Neoprene
Cable length	1 m
Cable designation	H07RN-F 5G1,5
Cable colour	black
Max. current carrying capacity	16 A
Residual current circuit breaker (RCCB)	Without
Protection	Without
CEE 400 V / 16 A / 3P+N+PE (5p) Steckdosen	3
Earthed socket outlets	3
Plug system socket	Type F (Protective contact)
Supply/ connection option	Supply cable with plug
Plug system plug	CEE 16 A 3P+N+E (5p) 400 V
Degree of protection (IP)	IP44

PACKAGING, DIMENSIONS AND WEIGHTS

Packaging	Neutral carton
UP	1
Weight of product (without packaging)	1.75 kg
Dimension LxWxH (without packing)	26 cm x 26 cm x 17 cm
Weight of product (including packaging)	1.76 kg
Dimension LxWxH (incl. packing)	26 cm x 26 cm x 17 cm

SCOPE OF DELIVERY

Compact power distributor BSV 3 LS E/16 2 IP44