Specifications

# Eaton 268999

## Catalog Number: 268999

Eaton Distribution parts, Fuse-link with blink application, D01, 16A, 24 V, gL/gG, set consists of 3 pieces




### General specifications

| | |
|---|---|
| **Product Name** | **Catalog Number** |
| Eaton Distribution parts | 268999 |
| **EAN** | **Product Length/Depth** |
| 4015082689995 | 45 mm |
| **Product Height** | **Product Width** |
| 80 mm | 54 mm |
| **Product Weight** | **Compliances** |
| 0.13 kg | RoHS conform |

Powering Business Worldwide

## Product specifications

### Used with

Z-SLS/CEK
Fuse links
Z-SLS/NEOZ
Z-SLK/NEOZ
Fuse material
Accessory
Fuse set

### Type

Accessory
Fuse material
Fuse set

### Special features

With flashing function
Snap-fit on DIN rail
1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator

### Amperage Rating

16 A

### Frame

D01

### Equipment heat dissipation, current-dependent

1.7 W

### Utilization category

gG (gL)
gL/gG (cable protection/equipment protection)

### Color

Gray

### Ambient operating temperature - max

55 °C

### Ambient operating temperature - min

-25 °C

### Heat dissipation capacity

0 W

### Heat dissipation per pole, current-dependent

## Resources

### Characteristic curve

1220DIA-6

1220DIA-7

### Declarations of conformity

DA-DC-03_Z-S

DA-DC-03_Z-S_SC_SB

DA-DC-03_Z-SLS-B

0 W

Rated operational current for specified heat dissipation (In)

16 A

Rated operational voltage (Ue) - max

24 V

Rated uninterrupted current (Iu)

16 A

Static heat dissipation, non-current-dependent

0 W

Test voltage

5 KV

Voltage rating at AC

24 - 60 V AC

Voltage rating at DC

24 - 60 V DC

Functions

Accessory

Voltage rating

24 V AC - 60 V AC

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia