Specifications

Eaton 100525

Catalog Number: 100525

Eaton Moeller® series E71 Proximity switch, optical, long range 2.5m, 4L, 10-30VDC, PNP, cable



General specifications

Product Name
Eaton Moeller® series E71 Proximity switch

Catalog Number
100525

EAN
4015081643325

Product Length/Depth
471.83 mm

Product Height
18.03 mm

Product Width
15.24 mm

Product Weight
0.24 kg

Certifications
UL Category Control No.: NRKH, NRKH7

Certified by UL for use in Canada
CE
UL 508
UL File No.: E166051
CSA File No.: UL report applies to both US and Canada
CSA-C22.2 No. 14
IEC/EN 60947-5-2
UL

Powering Business Worldwide

Product specifications

Type

Optical sensors

Features

Polarized light

Electric connection type

Cable

Enclosure material

Plastic

Enclosure type

Cuboid

Operating mode

Switching principle: Adjustable bright/dark switching

Explosion safety category for dust

None

Explosion safety category for gas

None

Functions

Short-circuit protection
Protection against polarity reversal
Reflected-light beam

Voltage type

DC

Connection type

2 m connection cable
4-wire

Light type

Polarized red light

Degree of protection

IP66
NEMA Other

Interface type

Other

LED indicator

Status indication of Switching state: Yellow LED
Status indication of Operating voltage: Green LED

Switch function type

Resources

Brochures

eaton-sensors-brochure-br053001en-en-us.pdf

Catalogs

Product Range Catalog Sensors – products, basic information, applications

Drawings

eaton-proximity-switches-proximity-switch-dimensions-023.eps

eaton-proximity-switches-e71-proximity-switch-3d-drawing-002.eps

Installation instructions

IL05305006Z

mCAD model

DA-CD-90_28292_001

DA-CS-90_28292_001

Other

Load current

Max. 100 mA (Ie)

Laser protection class

None

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Optical surface material

Plastic

Output current (mA) - max

100 mA

Output current at protected output - max

0 mA

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

Rated control supply voltage (Us) at DC - max

30 V

Rated control supply voltage (Us) at DC - min

10 V

Rated switching distance (Sn)

2500 mm

Reflector distance - min

0 mm

Sensor height

32 mm

Sensor length

20 mm

Switching distance - max

2500 mm

Switching voltage of OSSD at state high

30 V

Transmission range of the safety field

0 m

Voltage rating - max

30 V

Safety type (IEC 61496-1)

1

Switching frequency

500 Hz

Sensing mode

Light-/dark switching

Switching output type

PNP

Sensor material

Insulated material

Vibration resistance

10 - 55 Hz, Amplitude 0.5 mm

According to IEC/EN 60068-2-6

Wavelength of the sensor

660 nm

Width sensor

12 mm

Product category

E71 NanoView Series

Response time

1 ms

Ambient operating temperature - max

55 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

70 °C

Ambient storage temperature - min

-25 °C

Diameter sensor

0 mm

Light dot size

0 mm²

Number of contact energized outputs with signalling function

0

Number of outputs (protected contact energized)

0

Number of outputs (protected semiconductor)

0

Number of outputs (semiconductor with signaling function)

1

Operating temperature - max

55 °C

Operating temperature - min

-25 °C

Adjustment type

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia