

BTL6-A110-M0100-A1-S115
Ordering code: BTL001Y


Micropulse transducers
Series Profile

Output signal 0…10 V and 10…0 V
Nominal stroke 100 mm





Pin	
1	GND output
2	GND output
3	10...0 V
4	NC
5	0...10 V
6	GND
7	+24 V DC
8	NC



1) Not incl. in scope of del., 2) Unusable area, 3) Nom. stroke = Meas. length

Characteristic data

Output signal	0…10 V and 10…0 V
Connection	Connector, M12
Operating voltage	20...28 V DC

Electrical data

Ripple	0.5 Vpp
Current consumption (at 24 V DC)	≤ 70 mA
Inrush current	≤ 3 A / 0.5 ms
Overvoltage protected	Yes
Voltage-proof (GND – housing)	500 V DC
Ripple Ua max.	5
Galvanic isolation	No
For dynamic loop applications	No
Error signal Ua rising	≥ 10.2 V
Error signal Ua falling	≥ 10.2 V

Mechanical data

Version	Type A1
Mounting type	Mounting clamps
Connector type	M12
Cable/connector out	Axial
Number of pins	8
Housing material	Anodized aluminum
Resolution	≤ 10 µm
Repeat accuracy	≤ 10 µm
Sampling rate (length-depend.)	1 kHz, standard
TK, typ. (at 50% of 500 mm)	≤ 35 ppm/K
Ambient temperature Ta min.	0 °C
Ambient temperature Ta max.	70 °C
Storage temperature min.	-40 °C
Storage temperature max.	100 °C
Relative humidity	< 90%, non-condensing
Null point	73 mm

Basic data

Protected against polarity reversal	Up to 36 V
Enclosure Type per IEC 60529	IP67 (with connector)
EN 60068-2-27 (shock)	50 g / 6 ms
EN 60068-2-29 (cont. shock)	50 g / 2 ms
EN 60068-2-6 (vibration)	12 g, 10…2000 Hz
EN 60068-2-64 (noise)	5 g, 10…2000 Hz
EN 55016-2-3 (emission)	Class A+B
EN 61000-4-2 (ESD)	Severity Level 3
EN 61000-4-3 (RFI)	Severity Level 3
EN 61000-4-4 (burst)	Severity Level 3
EN 61000-4-5 (surge)	Severity Level 2
EN 61000-4-6 (HF fields)	Severity Level 3
EN 61000-4-8 (magnetic fields)	Severity Level 4
Approvals	CE, cURus

Remarks

Internet : www.balluff.com
Balluff Germany : +49 (0) 7158 173-0, 173-370
Balluff USA : 1-800-543-8390
Balluff China : +86 (0) 21-50 644131

BTL6-A110-M0100-A1-S115
Ordering code: BTL001Y

Micropulse transducers
Series Profile

Output signal 0…10 V and 10…0 V
Nominal stroke 100 mm