Resistant to oil, dust and water



UV-resistant

Application range
For a reliable sealing against foreign objects and liquids at the connecting thread of a gland or similar components.

Note
Delivery will be made in the largest possible packing unit (bulk goods), minimum order quantity is one packing unit

Remark
Perbunan® is a registered trademark of BAYER AG
Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Colour delivered:	Black
Material:	NBR Ozone and UV-resistant
Temperature range:	-20°C to +100°C

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.

Part number	Article designation / size	Inner Ø x thickness Ø (mm)
	SKINDICHT® O-Ring Perbunan®	
53001010	O 7	10 x 1,5
53102011	O 9	13 x 1,5
53001020	O 11	16 x 1,5
52005740	O 13,5	18 x 1,5
53001030	O 16	20 x 1,5
52005750	O 21	26 x 2
53001040	O 29	34 x 2
52005760	O 36	44 x 2
53001050	O 42	50 x 2
52005770	O 48	55 x 2

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.