Date: 11/04/2023

LH-20 ; 0...0.6 bar gauge; 4...20 mA + HART + PT100

LH-20 - High performance submersible pressure transmitter

Item number:	48782394
Quantity:	1 pcs.
Order code:	LH-20-BG260-CM0050-RM-S-ZZZZZK-Z-LSE-Z W1011LH2-PT5-ZZZEM
Overview:	LH-20 ; 0...0.6 bar gauge; 4...20 mA + HART + PT100 @ 9,6...30 V DC Accuracy: 0.2% of span Cable material: PE Cable length: 50 meter U+=BN, U-=BU / Pt100 supply = WH + BK / Pt100 signal = YE + RD Case material: stainless steel Process connection: M14x1 female with protection cap Sealing Sensor: dual EPDM (A+P 75.5/KW75F) certificate of potable water conformity: KTW, ACS Specifications according to data sheet: PE 81.56
Details:	LH-20 - High performance submersible pressure transmitter Specifications according to data sheet: PE 81.56 Measuring range: 0...0.6 bar gauge Cable material: PE Unit cable length: meter Cable length: 50 Output signal: 4...20 mA + HART + PT100 Accuracy: 0.2% of span Case material: stainless steel certificate of potable water conformity: KTW, ACS Process connection: M14x1 female with protection cap Sealing Sensor: dual EPDM (A+P 75.5/KW75F) pin assignment el. connection: U+=BN, U-=BU / Pt100 supply = WH + BK / Pt100 signal = YE + RD Power supply: 9,6...30 V DC

© 2023 - WIKA Instruments s.a.r.l.