Specifications

Eaton 229310



Catalog Number: 229310

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=160x100x80mm, +hinged cover CI-K2H-80-K

General specifications

Product Name
Eaton Moeller® series CI-K Insulated enclosure

Catalog Number
229310

EAN
4015082293109

Product Length/Depth
181 mm

Product Height
100 mm

Product Width
100 mm

Product Weight
0.36 kg

Certifications
IEC 60068-2-11
UL94: VO/1.5 mm thickness
IEC/EN 60529
DIN EN 62208
UL94: HB

Powering Business Worldwide

Product specifications

Type

Basic enclosure

Features

UV resistance beneath protective shield

Halogen free

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Not applicable.

10.2.6 Mechanical impact

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Meets the product standard's requirements.

Resources

Declarations of conformity

UKCA CI-K..-TS/M general purpose enclosures

CE CI-K..-TS/M general purpose enclosures

Drawings

eaton-small-enclosures-enclosure-ci-k-insulated-enclosure-dimensions-011.eps

eaton-small-enclosures-enclosure-ci-k-insulated-enclosure-dimensions-004.eps

eaton-small-enclosures-enclosure-ci-k-insulated-enclosure-dimensions-003.eps

eCAD model

DA-CE-ETN.CI-K2H-80-K

Installation instructions

IL01502081Z

mCAD model

DA-CD-ci_k_k

DA-CS-ci_k_k_2

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Is the panel builder's responsibility.

10.6 Incorporation of switching devices and components

Is the panel builder's responsibility.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

Fitted with:

Control cable entry

Hinged cover

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Enclosure material

Plastic

1 Ω x 10^{13} (Surface resistance to IEC 60093)

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

10 W

Heat dissipation per pole, current-dependent Pvid

0 W

Mounting depth

70 mm

Mounting weight capacity - max

0.7 kg

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

Product category

Empty enclosures

Enclosure color

Black (RAL 9005)
Light gray, Operator (RAL 7035)
Light gray, Cover (RAL 7035)

Environmental resistance

Not resistant to benzene
Resistant against gasoline
Not resistant to alkalis
Not resistant to Mineral oil
Resistant against alcohol
Resistant against benzene
Resistant against salt solutions
Resistant against alkalis
Resistant against greases
Resistant against mineral oil
Chemical resistant (Base, Cover)
Chemical resistant (Push-through membrane (CI-K1/CI-K2) and sealing material)
Partly resistant to greases
Resistant against acids (< 10%)
Partly resistant to acids (> 10%)
Partly resistant to alcohol
Partly resistant to benzene

Cover material

Glass-fiber reinforced polycarbonate

Degree of protection

IP65
NEMA Other

Model

Surface mounting

Dielectric strength

30 kV/mm, according to IEC 60243-1

Temperature resistance

-40 - 120 °C (enclosure)

-40 - 80 °C (gasket)

Suitable for

Emergency stop

Flammability characteristics

650 °C/1 mm thick (push-through membrane and seal material)
to VDE 0471 Part 2)
960 °C/1 mm thickness (base, cover; glow wire to VDE 0471
Part 2)

Knockouts

Hard knockout version
Metric cable entry knockouts at the top, bottom and back plate
Hard metric cable entry knockouts

Impact resistance

IK06 (according to EN 50102)

Surface treatment

Resistant to corrosion

Track resistance

CTI 175 (base, to IEC 60112)
CTI 175 (cover, to IEC 60112)

Water consumption

0.29 % (According to DIN EN ISO 62)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia