Specifications

# Eaton 058239

## Catalog Number: 058239

Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure. Connection terminal, 1000A, 3p, flat/round, 240



### General specifications

**Product Name**
Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure

**Catalog Number**
058239

**EAN**
4015080582397

**Product Length/Depth**
150 mm

**Product Height**
165 mm

**Product Width**
252 mm

**Product Weight**
12.685 kg

**Compliances**
RoHS conform

Powering Business Worldwide

## Product specifications

### Used with

Accessory panel building
General switchboard accessory

### Special features

Conversion kits for strip terminal in cable connection available separately
Terminal covers available separately
Including labels for terminal marking U, V, W - X, Y, Z - L1, L2, L3 - T1, T2, T3 - PE, N, PEN, protective earth (ground) symbol
Relationship of rated operational current →terminal capacity to IEC/EN 60439, VDE 0660 Part 500 or EN 50021
Outer terminal for round or sectoral conductor, other side for Cu strip

### Type

Accessory panel building
General switchboard accessory

### Features

Contact safe

### Accessory/spare part type

Terminations
Terminals, 160 – 1000 A

### Connection type

Clamp
Screwing

### Number of poles

Three-pole

### Rated operation current (Ie)

1000 A

## Resources

### Catalogs

eaton-panel-building-accessories-catalog-ca008008en-en-us.pdf

### Declarations of conformity

eaton-xeffect-k-type-terminals-declaration-of-conformity-en-us.pdf

### Drawings

eaton-control-panels-terminals-xeffect-k-type-terminal-3d-drawing.eps

### Installation instructions

IL015110ZU

### mCAD model

eaton-K3X240_3-3d-model.stp

eaton-K3X240_3-drawing.dwg

### System overview

eaton-control-panels-terminals-xeffect-k-type-terminal-explosion-drawing-002.eps

Mounting method

Screw

Suitable for

Useful for stranded conductors

Terminal capacity (copper band)

40 mm x 1 mm (10x) for flat strip

2 segments of 21 mm x 1 mm (11x) for flat strip

50 mm x 1 mm (10x) for flat strip

Nominal current

1000 A

Number of connections (Less Than 6 mm squared)

0

Number of connections (Less Than AWG 6)

0

Number of connections (Greater Than 25 mm squared)

6

Number of connections (Greater Than 250 kcmil)

0

Number of connections (10 mm squared)

0

Number of connections (16 mm squared)

0

Number of connections (25 mm squared)

0

Number of connections (250 kcmil)

0

Number of connections (AWG 2)

0

Number of connections (AWG 4)

0

Number of connections (AWG 4/0)

0

Number of connections (AWG 6)

0

Number of connections (total)

6

Rated insulation voltage (Ui)

1000 VAC

Number of outputs

3

Terminal capacity (aluminum cable)

150 mm² - 185 mm² (3x)

150 mm² - 240 mm² (2x)

Terminal capacity (conductor)

60 mm x 15 mm

Terminal capacity (copper/aluminum cable)

150 mm² - 300 mm² (2x)

50 mm² - 240 mm² (3x)

Conductor cross section, input - max

300 mm²

Conductor cross section, output - min

50 mm²

Conductor cross section, input - min

50 mm²

Conductor cross section, input AWG - min

1 mm²

Conductor cross section, input AWG - max

600 mm²

Conductor cross section, output - max

300 mm²

Conductor cross section, output AWG - max

0 mm²

Conductor cross section, output AWG - min

0 mm²

Number of inputs

2




Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia