Date: 12/04/2023

RLS-1000; Guide tube length: 1000.0; 1 switching output

RLS-1000; Guide tube length: 1000.0; 1 switching output

Item number:	48791675
Quantity:	1 pcs.
Order code:	RLS-10003M101000ZZZZZZZZZZZZZZZZZZZ1GZ8J100004ZD Z1W101ARS1ZL4
Overview:	RLS-1000; Guide tube length: 1000.0; 1 switching output Magnetic float switch, Stainless steel version Model RLS-1000 Output Signal: 1 switching output Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 100 mm Electrical connection: Circular connector M12x1, IP65 pin assignment el. connection: see product label Process connection: G1/2, installation from outside Guide tube length: 1000.0 mm medium temperature: -30 °C ... 80 °C Wetted parts: Stainless steel 1.4571 Float: Cylindrical float Ø 18 mm, Buna/NBR, PN16 Specifications according to data sheet: LM 50.03
Details:	RLS-1000; Guide tube length: 1000.0; 1 switching output Magnetic float switch, Stainless steel version Model RLS-1000 Output Signal: 1 switching output Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 100 mm Electrical connection: Circular connector M12x1, IP65 pin assignment el. connection: see product label Process connection: G1/2, installation from outside Guide tube length: 1000.0 mm medium temperature: -30 °C ... 80 °C Wetted parts: Stainless steel 1.4571 Float: Cylindrical float Ø 18 mm, Buna/NBR, PN16 Specifications according to data sheet: LM 50.03

© 2023 - WIKA Instruments s.a.r.l.