

PRODUCT NUMBER: 1032373

# Miller kernmantel edge shock absorbing lanyard 1,5 meters with a twist lock + GO55 karabiner.

Miller kernmantel edge shock absorbing lanyard 1,5 meters with a steel twist lock and a GO55 steel scaffold hook karabiner.

## Overview

**Reference Number**
1032373

**Product Type**
Fall Protection

**Range**
Shock Absorbing Lanyards

**Line**
Cut resistant

**Brand**
Miller by Honeywell

**Industry**

- Building and Construction

**Product Use**

Fall arrest lanyards will allow the worker to fall but prevents him from hitting the next lower level, such as the ground, (if well attached). It includes a shock absorber that dissipates the forces exerted on the body in the case of a fall to stay below 6 KN.

This single lanyard is edge tested for safe working  on edges (r>= 0,5 mm).

## Features & Benefits

**Feature**
New design : * Lanyard manufactured with a light green rope with black stripes, which are highly visible from a distance increasing safety at work. * The stitches are highly visible which facilitates the safety check before use.

**Benefit**
* Lanyard edge tested : manufactured with hight quality kernmantel rope and have special. * The rope is 2 times more resistant to the abrasion than the other standard ropes.


© Honeywell International Inc.

## Technical Description

**Length**
1,5 M

**Weight**
0,990 KG

**Breaking Strength**
> 22 KN

**Operating Temperature**
-30°c to +50°C

### Rope

**Rope Raw Material**
Kernmantel Ø 11 mm polyester sheath and polyamide core

### Connector

**Connector Type**
Twist lock karabiner

**Connector Raw Material**
steel

**Connector Opening**
17 mm

**Connector Breaking Strength**
> 22 KN

**Connector Standard**
EN 362 : 2004

### Connector

**Connector Type**
GO55 scaffold hook

**Connector Raw Material**
steel

**Connector Opening**
55 mm

**Connector Breaking Strength**
> 25 KN

**Connector Standard**
EN 362 : 2004

### Energy Absorber

**Energy Absorber Raw Material**
Resistant webbing shock absorber with protective cover

## Certifications

**E.C. Declaration of Conformity**

**EC Category PPE**
3

**Quality Assurance**
ISO 9001 / 2000

**EC Attestation**
EC Attestation

**EC Attestation Number**
0082-490-160-06-13-0169

**Certifications**

- EN 355 / VG 11 PFE 11.074

**REACH**

**EU Regulation 1907/2006 (REACH) Compliance**


© Honeywell International Inc.

| The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article. | |
|---|---|
| **Product Reference Sold in Europe** | **Substance > 0.1%** |
| **Substance Name** | **CAS Number** |
| No Substance Content | |

## Additional Information

**User Manual**
NT90004208 IND L

**User Information Sheet**
User manual

## Maintenance

**Life Cycle**
Life expectancy of our lanyards is 10 years from the date of manufacture.

**Care Instructions**
Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Please remember that:
- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.

© Honeywell International Inc.


© Honeywell International Inc.

apave
Centre d'Essais de Fontaine
17, Boulevard Paul Langevin
38600 FONTAINE - France
Tél. +33.(0)4.76.53.52.22
Fax +33.(0)4.76.53.32.40
lab38chute@apave.com

En exécution de la directive 89/686/CEE du 21 décembre 1989 modifiée concernant le rapprochement des législations des états membres relatives aux équipements de protection individuelle et des dispositions pertinentes du code du travail, portant transposition de cette directive en droit français,
*In enforcement of amended directive 89/686/EEC of 21st of December 1989 on the approximation of the laws of the Members States relating to personal protective equipment and in enforcement of relevant requirements of the French labour code, providing for the transcription of this directive into French regulations,*

APAVE SUDEUROPE SAS, organisme notifié, identifié sous le numéro 0082, attribue l'
*APAVE SUDEUROPE SAS, notified body, identified under number 0082, awards the*

# ATTESTATION D'EXAMEN CE DE TYPE
## *(EC Type examination certificate)*
## N° 0082/490/160/06/13/0169

A l'équipement suivant :
*To the following equipment:*

➢ Type d'équipement : **EPI de catégorie III - Absorbeur d'énergie**
*Category of equipment: PPE category III - Energy absorber*

➢ Marque commerciale : **MILLER®**
*Trademark*

➢ Equivalence : la présente attestation est attribuée aux deux modèles suivantes :
*Equivalence: this certificate is awarded to the two following models:*

- Modèle : **LONGE ABSORBEUR DRISSE NUE** : Absorbeur d'énergie intégrant une longe simple fixe
  *Model* — *Energy absorber integrating a fixe single lanyard*
- Modèle : **LONGE ABSORBER DRISSE XM+CONNECTEURS** : Absorbeur d'énergie intégrant une longe fixe simple avec connecteurs
  *Model* — *Energy absorber integrating a fixe single lanyard with connectors*

➢ Fabricant : HONEYWELL FALL PROTECTION France SAS – 35-37 Rue de la Bidauderie – 18100 VIERZON Cedex France
*Manufacturer*

➢ Description : Absorbeur d'énergie à sangle à déchirement, en polyamide 6, largeur 30 mm, longueur 0,18 m, protégé par une gaine thermoretractable, intégrant une longe fixe simple en cordage polyester/polyamide, diamètre 11 mm. A chaque extrémité de la longe, une boucle cousue cossée, soit de référence 90001626, soit 90022716, protégée par une gaine thermoretractable de référence 90002874 ou 90022718. L'absorbeur d'énergie peut être équipé des connecteurs intégrés suivant : 1006452 ou 1018973 ou 1018972 ou 1018977 ou 1009249 ou 1018976 ou 1029701 ou 1004300. Longueurs disponibles de 0.5 m à 2m (description détaillée dans le rapport d'examen CE de type 13.6.0234).

*Description: Energy absorber with wrench webbing, in polyamide 6, width 30 mm, length 0.18 m, protected by a thermoretractable sheath integrating a single fixe lanyard rope, in polyester/polyamide, diameter 11mm. On each end of lanyard, a sewn thimbled buckle, either of reference 90001626 or 90022716 protected by a thermoretractable sheath of reference 90002874 or 90022718. The energy absorber can be equipped with integrated connector of reference: 1006452 or 1018973 or 1018972 or 1018977 or 1009249 or 1018976 or 1029701 or 1004300. Available lengths from 0.5m to 2m (detailed description in EC type examination report 13.6.0234).*

➢ Référentiel technique utilisé : EN 355 : 2010.
*Technical referential used*

Date : 6 juin 2013
*Date: the 6th June 2013*

Document authentifié par tampon sec
*Document certified by dry stamp*

Le Responsable du Centre d'Essais de Fontaine – Certification EPI
*Head of Fontaine Testing Centre – PPE Certification*

Vincent MAILLOCHEAU

NOTA : Toute modification apportée au matériel neuf objet de la présente attestation d'examen CE de type doit être portée à la connaissance de l'organisme habilité en application de l'article R4313-38 du code du travail.
*Any modification brought about a new equipment covered by this CE type examination certificate must be notified to the body in enforcement of article R4313-38 of French labour code.*

Cette attestation comporte une page. Elle est établie en deux exemplaires originaux transmis au demandeur. Aucun duplicata ne sera délivré.
*This certificate includes one page. This certificate is edited in two original copies. No duplicate will be issued.*

# E.C. Declaration of Conformity

**The manufacturer or its legal representative supplier in the European Community:**
Honeywell Safety Products Europe

**Declares that the Personal Protective Equipment described here after conforms to the provisions of the European Council Directive 89/686/CEE:**
Designation: Miller kernmantel edge shock absorbing lanyard 1,5 meters with a twist lock + GO55 karabiner.
Reference: 1032373
Standard(s): EN355

**This PPE is the object of the below EC examination certificate n°:**

**And is subject to the procedure set out in Article 11 point B of Directive 89/686/EEC under the supervision of the below notified body.**

**Delivered by:**
APAVE SUDEUROPE SAS
BP 3
33370
ARTIGUES près BORDEAUX
France

Drawn up in , on the 17/06/2015
**By**: Frederic Wagner
**Division**: Fall Protection



Zl Paris Nord II 33, rue des Vanesses BP 50288 95958 Roissy CDG France
Tel: +33 (0) 49 90 79 79 Fax: +33 (0)1 49 90 79 80
www.honeywellsafety.com