Sealing for Appliance Inlets



6100 with sealing to appliance

Description
- Protects from ingressing fluids and dust into the appliance
- 1 Function

Weblinks
pdf-datasheet, html-datasheet, General Product Information, Approvals, CE declaration of conformity, RoHS, CHINA-RoHS, REACH, Mating Connectors, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check, CAD-Drawings, Accessories, Detailed request for product

Assembly Instructions



Panel thickness max. 3 mm
Tightening torque max 0.1 Nm
1 Chassis
2 Appliance inlet
3 Flat gasket (included in 0098.0103)
4 Srew with sealing (included in 0098.0103)
5 Lock washer (not part of kit)
6 Nut 0.8d (not part of kit)

1) Mounted from rear side



Panel thickness max. 3 mm
Tightening torque max 0.1 Nm

All Variants

Suitable for	Degree of Protection	Mounting side	Mounting instruction	Mounting option	Order Number
6100-3, 6120-3	IP 54	Front-/Rear-Side	1)	Screws included	0098.0103

03.03.2015

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.