*Date: 11/04/2023*

# F73.100/1, 0...100°C, L1=100 mmx8mm,

## Gas actuated thermometer, stainless steel series

Item number: 48731326

Quantity: 1 pcs.

Order code: F73.100-C1E-1BK-C0100-S01-4-Z-HZZ-ZZZZZZ G7 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ

Overview:
F73.100/1, 0...100°C, L1=100 mmx8mm,
plain, without thread axial
Surface mounting bracket, die cast aluminium
stainless steel armoured capillary
Capillary length: 1 m
laminated safety glass
class 1 per EN 13190
*WIKA*
with Serial number

Details:
Gas actuated thermometer, stainless steel series
Specifications according to data sheet: TM 73.01
Case: stainless steel
Stem material: stainless steel
Model: F73.100, nominal size 100, with capillary
Unit: °C
Scale range: 0 °C ... 100 °C
Connection design: 1, plain stem
Process connection: plain, without thread
Stem diameter: 8 mm
Insertion length L1: 100 mm
Capillary: stainless steel armoured capillary
Capillary length: 1 m
Design of case mounting: Surface mounting bracket, die cast aluminium
Ignition protection type: without
Zone: without
Accuracy class: class 1 per EN 13190
Ingress protection: IP 65
Window: laminated safety glass
Case: Stainless steel
Connector location: axial
Manufacturer logo: *WIKA*
Permissible ambient temperature: -40 … +60 °C
with Serial number

*© 2023 - WIKA Instruments s.a.r.l.*