PRODUCT-DETAILS

OT25F8

OT25F8 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT25F8
Product ID	1SCA104882R1001
EAN	6417019390253
Catalog Description	OT25F8 SWITCH-DISCONNECTOR
Long Description	8-pole, front operated, base mounted, DIN-rail mountable switch-diconnector / non-fusible diconnect switch with protected clamp terminals, handle and shaft are not included

ABB EcoSolutions

Environmental Information	1SCC301262D0201
Environmental Product Declaration - EPD	1SCC301278D0201

Material Compliance

Conflict Minerals	9AKK108467A5658

© 2024 ABB. All rights reserved.

Reporting Template (CMRT)	
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301055M0003
Mechanical Drawings	1SCC301444F0001 1SCC301443F0001 OT16-40F8.stp OT16-40F8.igs
Environmental Product Declaration - EPD	1SCC301278D0201

Environmental

Degree of Protection	Front IP20
Environmental Information	1SCC301262D0201
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	96 mm
Product Net Height	68 mm
Product Net Depth / Length	68 mm
Product Net Weight	0.27 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	80 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	80 mm
Package Level 1 Gross Weight	0.31 kg
Package Level 1 EAN	6417019390253

© 2024 ABB. All rights reserved.

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 20 A (500 V) 20 A (690 V) 11 A
Rated Operational Current DC-21B (I_e)	(750 V) 25 A (550 V) 25 A (800 V) 16 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 4 kW (400 ... 415 V) 9 kW (500 V) 9 kW (690 V) 9 kW
Conventional Free-air Thermal Current (I_{th})	Θ = 40 °C 32 A
Conventional Thermal Current (I_{the})	Fully Enclosed 32 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 0.71 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 0.5 kA
Rated Conditional Short-Circuit Current (I_{nc})	(40 A fuse, ≤415V) 50 kA (25 A fuse, 690 V) 50 kA
Power Loss	at Rated Operating Conditions per Pole 0.6 W
Pollution Degree	3
Handle Type	Knob Handle and shaft not included
Fourth Pole Position	Left and Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Special Functions	No
Mounting Type	Base mounting
Number of Poles	8
Connecting Capacity Main Circuit	Flexible with Ferrule 1x Cu 0.75…4 mm² Solid 1x Cu 0.75…6 mm² Flexible 1x Cu 0.75…10 mm² Stranded 1x Cu 0.75…10 mm²
Cable Cross-Section	Cu 0.75 ... 10 mm²
Wire Stripping Length	Main Circuit 9-10 mm
Recommended Screw Driver	Main Circuit Pozidriv 2

© 2024 ABB. All rights reserved.

Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Mechanical Durability	20000
Lock Type	No

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	30 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 1.5 Hp (240 V AC) Single Phase 3 Hp (440 ... 480 V AC) Single Phase 7.5 Hp (550 ... 600 V AC) Single Phase 10 Hp (220 ... 240 V AC) Three Phase 7,5 Hp (440 ... 480 V AC) Three Phase 15 Hp (550 ... 600 V AC) Three Phase 20 Hp
Wire Stripping Length	Main Circuit 9-10 mm
Recommended Screw Driver	Main Circuit Pozidriv 2
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Tightening Torque UL/CSA	7 in·lb

Certificates and Declarations

A2L Certificate – IEC	1SCC301335D0201
ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301166D2703
UL Certificate	cULus certificate OT16-80
VDE Certificate	No certification needed

Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601434
E-Number (Norway)	4363570

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors



© 2024 ABB. All rights reserved.