POLYAMIDE (PA) RECOIL TUBING

Email Print



Parker Legris recoil tubing has a lasting memory after multiple uses, offering an alternative to reels for excellent ergonomics and space saving.
The pre-assembled tubes are equipped with a protection spring, preventing damage to the ends.

PART NUMBER:
1471P08 07 13

TUBING MATERIAL:
PA

TUBE I.D. (MM):
6

TUBE O.D. (MM):
8

CONNECTION 1 THREAD SIZE (METRIC):
R1/4

COLOR:
ORANGE

LENGTH (M):
4

Reset Attributes

WHERE TO BUY

PRODUCT OVERVIEW -

TECH SPECIFICATIONS +

Print Tech Specifications

PERFORMANCE CHARACTERISTICS

MAXIMUM PRESSURE (BARG)

20

MINIMUM WORKING TEMPERATURE (°C)

-20

MAXIMUM WORKING TEMPERATURE (C)

80

VACUUM RATING (MM OF HG)

755

WEIGHT (KG/PACKAGE)

0.249

NUMBER OF TUBES

1

APPLICATION

MRO, Pneumatic Tools, Transportation, Lubrication, Industrial Cleaning, Robotics, Car Washing

MEDIA

Compressed air, lubricants, Other fluids: please consult us

CERTIFICATES

DI: 97/23/EC (PED), RG: 1907/2006 (REACH), DI: 2002/95/EC (RoHS), 2011/65/EC

Print Tech Specifications

CAD +

PRODUCT SUPPORT +

RECOMMENDED



C 9000 Polymer Quick-Acting Safety Couplers



Polyurethane (PU) Recoil Tubing



Braided Polyurethane (PU) Recoil Hose

CONTACT US

Parker Hannifin Manufacturing France SAS

Fluid System Connectors Division Europe
Parc Alcyone - Bat. D
1 rue André et Yvonne Meynier - CS 46911
35069 Rennes Cedex France

Phone
Phone: +33 (0) 2-99-25-55-00

EMAIL PARKER

Parker Hannifin +

Products
About Parker
Investors
Community
Careers

Global Operations +

Divisions
Sales Companies
Worldwide Locations
Distribution Network