
2CSC400325F0201


2CSC400055F0201


2CSC400023F0201

S 2C-S6R U


2CSC400024F0201

S 2C-H6R U


2CSC400013F0201

S 2C-A1 U


2CSC400097F0201

PS 3/6/16 BP

Undervoltage release

Function: protection of the load in the event of a voltage drop (between 70% and 35% of its rated value); positive safety (device's tripping when the voltage is disconnected) emergency stop by means of a button. Suitable for MCBs S 200 series, RCBOs DS 200 series.

Rated voltage	Order details		Bbn 8012542	Price 1 piece	Price group	Weight 1 piece	Pack unit
	Type code	Order code	EAN			kg	pc.
12VDC	**S2C-UA 12 DC**	2CSS200911R0001	**839705**			0.09	1
24VAC	**S2C-UA 24 AC**	2CSS200911R0002	**839804**			0.09	1
24VDC	**S2C-UA 24 DC**	2CSS200911R0007	**896401**			0.09	1
48VAC	**S2C-UA 48 AC**	2CSS200911R0003	**839903**			0.09	1
48VDC	**S2C-UA 48 DC**	2CSS200911R0008	**896500**			0.09	1
110VAC	**S2C-UA 110 AC**	2CSS200911R0004	**840008**			0.09	1
110VDC	**S2C-UA 110 DC**	2CSS200911R0009	**896609**			0.09	1
230VAC	**S2C-UA 230 AC**	2CSS200911R0005	**840107**			0.09	1
230VDC	**S2C-UA 230 DC**	2CSS200911R0010	**896708**			0.09	1
400VAC	**S2C-UA 400 AC**	2CSS200911R0006	**840206**			0.09	1

Hand operated neutral

The hand operated neutral has to be mounted to the left side of the MCB and be snaped on the DIN rail. It is used for measuring duties where the neutral conductor must be in the open position. Due to the special design of the handle - when switching ON the MCB – the neutral will make before the MCB is closed.
The S2C - Nt is not to switch with a tool (screw driver).

Description	Order details		Bbn 4016779	Price 1 piece	Price group	Weight 1 piece	Pack unit
	Type code	Order code	EAN			kg	pc.
Max 40A	**S2C-Nt**	2CDS200918R0001	**647625**			0.06	1

Accessories for S 200 U and S 200 UP acc. UL 489 and CSA-22.2 No. 5

Auxiliary contact (switch)

only for range U and UP	**S 2C-H6R U**	2CDS 200 914 R0001	**61561 7**			0.035	1

Signal contact (bell alarm)

only for range U and UP	**S 2C-S6R U**	2CDS 200 924 R0001	**64677 2**			0.035	1

Shunt trip only for range U and UP

12 - 60 V AC/DC	**S 2C-A1 U**	2CDS 200 908 R0001	**64472 3**			0.15	1
110-415 V AC,110-250V DC	**S 2C-A2 U**	2CDS 200 908 R0002	**64473 0**			0.15	1

Conn. capacity	Lenght	No. of poles	Order details		Bbn 4016779	CuNo 1 piece	Price 1 piece	Price group	Weight 1 piece	Pack unit
mm^2	mm		Type code	Order code	EAN				kg	pc.

UL-approved busbar blocks (not to be cut)

1 pole busbars, spacing 17.5 mm, UL 489

16	6	1	**PS 1/6/16 BP**	2CDL 210 489 R1606	**64496 9**	0.035			0.058	1
16	12	1	**PS 1/12/16 BP**	2CDL 210 489 R1612	**64497 6**	0.070			0.108	1
16	18	1	**PS 1/18/16 BP**	2CDL 210 489 R1618	**64498 3**	0.105			0.163	1