Specifications

Eaton 50NHG000B-400

Catalog Number: 50NHG000B-400

Fuse-link, LV, 50 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs

General specifications

Product Name
Eaton Bussmann series low voltage NH Fuse

Catalog Number
50NHG000B-400

EAN
5027590483155

UPC
051712233347

Product Length/Depth
79 mm

Product Height
51 mm

Product Width
21 mm

Product Weight
119 g

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60269
IEC 60269-2
EAC
VDE

Product specifications

Type
Fuse

Application
industrial

Amperage Rating
50 A

Current type
AC

Breaking capacity
120 kA

Frequency rating - max
62 Hz

Frequency rating - min
45 Hz

Rated switching capacity
120 kA

Rated voltage AC
400 V

Class
Class gG/gL

Fuse type
Square body with knife blade contact

Utilization category
gL/gG (cable protection/equipment protection)

Interrupt rating
120 kAIC

Fuse indicator
Combination fuse status indicator

Insulated metal gripping lugs (IMGL)
No

Watt losses
3.4 W

Connection
Blade end

Construction

Resources

Catalogs
eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

NH Fuse links, bases and gear

CA134002EN

Declarations of conformity
CE NH Size 000, 400V fuse-links

UKCA NH Size 000, 400V fuse-links

Multimedia
Eaton Bussmann – NH fuse link portfolio

Presentations
NH Overview Video

Technical data sheets
720099 NH 400 Volts gG

NH000

Construction size

NH000

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Packaging type

Standard

Quantity

3

Voltage rating

400 V

Rated switching capacity AC

120 kA

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia