Rittal – The System.

Faster – better – everywhere.

Air duct system for roof-mounted cooling units and roof-mounted air/water heat exchangers – SK 3286.970

Date : Apr 26, 2021

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Air duct system for roof-mounted cooling units and roof-mounted air/water heat exchangers – SK 3286.970

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	Cold air may be routed directly to specific areas of the enclosure using the air duct system. The risk of air short circuits due to self-ventilated installed devices is therefore eliminated. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to the required length.
Material:	Flame-resistant plastic to DIN 4102/B1
Colour:	RAL 7035
Supply includes:	Shallow duct Compensating hose
Note:	Do not direct cold air straight at active components. When using the ducting system, the performance of the cooling unit may be reduced, depending on the application in question. For devices 3359..../3382...., the air duct adaptor 3286.840 is additionally required.
To fit Model No.:	3386.... 3387....

Product description

eCl@ss 8.0/8.1:	22410601
Packs of:	1 pc(s).
Weight/pack:	4.05 kg

EAN:	4028177325456
Customs tariff number:	39269097
ETIM 7.0:	EC011444
ETIM 6.0:	EC001292
eCl@ss 8.0/8.1:	22410601
eCl@ss 6.0/6.1:	27189269
Product description:	SK Air duct system, for SK 3209/3210/3273/3359/3382/3383/3384/3385, WHD: 229 x 1500 x 29 mm

Approvals

Certificates:	EAC