
TIMKEN

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number LM501349 - LM501311, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Basic Load Ratings | Factors

Specifications

Series	LM501300
Cone Part Number	LM501349
Cup Part Number	LM501311
Design Units	Imperial
Bearing Weight	0.400 Kg 0.80 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	41.275 mm 1.6250 in
D - Cup Outer Diameter	73.431 mm 2.8910 in

B - Cone Width	19.812 mm 0.7800 in
C - Cup Width	18.186 mm 0.7160 in
T - Bearing Width	23.012 mm 0.9060 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius[1]	3.560 mm 0.14 in
r - Cup Backface "To Clear" Radius[2]	2.29 mm 0.090 in
da - Cone Frontface Backing Diameter	48.01 mm 1.89 in
db - Cone Backface Backing Diameter	54.10 mm 2.13 in
Da - Cup Frontface Backing Diameter	71.10 mm 2.80 in
Db - Cup Backface Backing Diameter	64.01 mm 2.52 in
Ab - Cage-Cone Frontface Clearance	1.8 mm 0.07 in
Aa - Cage-Cone Backface Clearance	0.3 mm 0.01 in
a - Effective Center Location[3]	-3.30 mm -0.13 in


Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)[4]	19400 N 4360 lbf
C1 - Dynamic Radial Rating (1 million revolutions)[5]	74800 N 16800 lbf
C0 - Static Radial Rating	74200 N 16700 lbf
C_{a90} - Dynamic Thrust Rating (90 million revolutions)[6]	13300 N 2980 lbf

Factors

K - Factor[7]	1.46
e - ISO Factor[8]	0.40
Y - ISO Factor[9]	1.5
G1 - Heat Generation Factor (Roller-Raceway)	23.3
G2 - Heat Generation Factor (Rib-Roller End)	13.3
Cg - Geometry Factor	0.0739

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These maximum fillet radii will be cleared by the bearing corners.
[3] Negative value indicates effective center inside cone backface.
[4] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.
[5] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.
[6] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.
[7] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[8] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[9] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e	0.4	
ISO Factor - Y	1.5	
Bearing Weight	0.8	lb
Number of Rollers Per Row	19	
Effective Center Location	-0.13	inch

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

LM501349 - LM501311
TS BEARING ASSEMBLY

K Factor	1.46	
Dynamic Radial Rating - C90	19400	lbf
Dynamic Thrust Rating - Ca90	13300	lbf
Static Radial Rating - C0	74200	lbf
Dynamic Radial Rating - C1	74800	lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY