Date: 11/04/2023

DW-40US - 0...400 mbar - 2x1/4 -NPT-F - 1/2 -14 NPT-F

Differential pressure switch, Stainless steel version

Item number: 48791529

Quantity: 1 pcs.

Order code: DW-40-US-MANC-BAMZZZAAZZZ ZCW
M022000DZZZZZZZZ

Overview:
DW-40US - 0...400 mbar - 2x1/4 -NPT-F - 1/2 -14 NPT-F
Differential pressure switch, Stainless steel version DW
40 bar
Contact version: 1x SPDT silver contact, hermetically sealed, argon gas filling
setting range: 0...400 mbar
Set point definition: Set Point customer-specifically configured
Process connection: 2x1/4 -NPT-F
Electrical connection: 1/2 -14 NPT-F
Mounting: Enclosure with plate for wall or direct mounting
Diaphragm Material: AISI 316
Brand: WIKA Instruments Italia
Connection: Stainless steel AISI 316L
Specifications according to data sheet: PV 35.42
Repeatability of set point: ≤ 1% of span

1. set point: 220.00 mbar decreasing,

Details:
Differential pressure switch, Stainless steel version
Models DW and DW10
Specifications according to data sheet: PV 35.42
Repeatability of set point: ≤ 1% of span
static and one-side pressure: 40 bar
Contact version: 1x SPDT silver contact, hermetically sealed, argon gas filling
setting range: 0...400 mbar
Set point definition: Set Point customer-specifically configured
Process connection: 2x1/4 -NPT-F
Electrical connection: 1/2 -14 NPT-F
Mounting: Enclosure with plate for wall or direct mounting
Diaphragm Material: AISI 316
Brand: WIKA Instruments Italia
Connection: Stainless steel AISI 316L
DW-40US
1. set point: 220.00 mbar decreasing,

© 2023 - WIKA Instruments s.a.r.l.