Date: 24/01/2024

S-20 ; 0...1000 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V

S-20 ; 0...1000 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V

Item number:	14071213
Quantity:	1 pcs.
Order code:	S-20-3-BG610-HSC3K-F-AGGZZZ-ZWZ W1011S20Z-ZZZZA1Z3-SS1CLZ3APSZZE-ZZGDZZSAZZZS1
Overview:	S-20 ; 0...1000 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V Pressure transmitter Model S-20 Non-linearity: 0.25% BFSL Overpressure limit: see data sheet Process connection: G 1/2 B EN 837 ; Sealing: copper Pressure port: D 2.5 mm Electrical connection: angular connector DIN 175301-803 A mating connector included pin assignment el. connection: U+=1, U-=2, S+=3 Permissible medium temperature: -30...+100°C shock and vibration resistance: 100 g shock, 20 g vibration Approvals: cULus Test protocol: with test protocol
Details:	S-20 ; 0...1000 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V Pressure transmitter Model S-20 Non-linearity: 0.25% BFSL Overpressure limit: see data sheet Process connection: G 1/2 B EN 837 ; Sealing: copper Pressure port: D 2.5 mm Electrical connection: angular connector DIN 175301-803 A mating connector included pin assignment el. connection: U+=1, U-=2, S+=3 Permissible medium temperature: -30...+100°C shock and vibration resistance: 100 g shock, 20 g vibration Approvals: cULus Test protocol: with test protocol

© 2024 - WIKA Instruments s.a.r.l.