# SELF-FASTENING NITRILE BUTADIENE RUBBER (NBR) HOSE

Email Print



Parker Legris self-fastening hose is designed according to CNOMO E07.21.115N*.
This range of hose should be used with Legris barb connectors and provides both the reliability of self-fastening technology and simplicity of installation.

**PART NUMBER:**
1040H66 02

**TUBING MATERIAL:**
NITRILE - TEXTILE

**TUBE I.D. (MM):**
15,9

**TUBE O.D. (MM):**
23

**COLOR:**
GREEN

**DIAMETER NOMINAL (DN):**
5/8

**LENGTH (M):**
40

Reset Attributes

WHERE TO BUY

## PRODUCT OVERVIEW -

## TECH SPECIFICATIONS +

Print Tech Specifications

### PERFORMANCE CHARACTERISTICS

**MAXIMUM PRESSURE (BARG)**

16

**MINIMUM WORKING TEMPERATURE (°C)**

-20

**MAXIMUM WORKING TEMPERATURE (C)**

100

**WEIGHT (KG/PACKAGE)**

14

**MAXIMUM BEND RADIUS (MM)**

140

**NUMBER OF TUBES**

1

**APPLICATION**

In-Plant Automotive, Cooling, Welding Robots, Pneumatics, Industrial Machinery

**MEDIA**

Coolants, compressed air

**CERTIFICATES**

NFT 46-019-1, NFT 47 252, RG: 1907/2006 (REACH), DI: 2002/95/EC (RoHS), 2011/65/EC, CNOMO: E07.21.115N//*CAUTION: CNOMO certification is valid exclusively for red and green hose, only when connected to Legris' CNOMO-certified barb connectors 0132, 0133

Print Tech Specifications

## PRODUCT SUPPORT +

## RECOMMENDED



Adaptors, Plugs and Manifolds

## CONTACT US

**Parker Hannifin Manufacturing France SAS**

Fluid System Connectors Division Europe
Parc Alcyone - Bat. D
1 rue André et Yvonne Meynier - CS 46911
35069 Rennes Cedex France

**Phone**
Phone: +33 (0) 2-99-25-55-00

EMAIL PARKER

## Parker Hannifin +

Products
About Parker
Investors
Community
Careers

## Global Operations +

Divisions
Sales Companies
Worldwide Locations
Distribution Network