# DATASHEET - DX-CBL-RJ45-1M0

**Cable for variable frequency drives (1 m, RJ45/RJ45)**

| | |
|---|---|
| **Part no.** | **DX-CBL-RJ45-1M0** |
| | **169138** |
| **EL Number (Norway)** | **4137455** |

## General specifications

| | |
|---|---|
| Product name | Eaton DX Connection cable |
| Part no. | DX-CBL-RJ45-1M0 |
| EAN | 4015081656172 |
| Product Length/Depth | 38 millimetre |
| Product height | 170 millimetre |
| Product width | 120 millimetre |
| Product weight | 0.1 kilogram |
| Certifications | IEC/EN61800-5<br>UL Category Control No.: NMMS, NMMS7<br>UL File No.: E172143<br>UL 508C<br>CSA-C22.2 No. 14<br>IEC/EN61800-3<br>CE<br>UL report applies to both US and Canada<br>Certified by UL for use in Canada<br>UL |
| Product Tradename | DX |
| Product Type | Accessory |
| Product Sub Type | Connection cable |

## General information

| | |
|---|---|
| Accessory/spare part type | Cable |
| Degree of protection | IP00 |
| Product Category | Accessories |
| Suitable for | Branch circuits, (UL/CSA) |
| Type | Patch cord with RJ45 plugs, 8 pole |
| Used with | DE1<br>DC1<br>DA1<br>DB1 |

## Climatic environmental conditions

| | |
|---|---|
| Ambient operating temperature - max | 50 °C |
| Ambient operating temperature - min | -10 °C |

## Design verification

| | |
|---|---|
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Meets the product standard's requirements. |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |

| | | | |
|---|---|---|---|
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 9.0

| | | | |
|---|---|---|---|
| Low-voltage industrial components (EG000017) / Accessories/spare parts for frequency controller (EC002025) | | | |
| Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter (accessories) (ecl@ss13-27-02-31-92 [AFR303008]) | | | |
| Type of accessory/spare part | | | Cable |
| Accessory | | | Yes |
| Spare part | | | No |


© 04/2023 by Eaton Industries GmbH