DATASHEET - 500V 800A NH4 FUSE AG



Fuse-link, low voltage, 800 A, AC 500 V, 120 kA, NH4, gL/gG, IEC, single indicator, live gripping lugs

Powering Business Worldwide

Part no.	**500V 800A NH4 FUSE AG**
Catalog No.	**800NHG4G**
EL-Nummer (Norway)	**1664092**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	800
Rated voltage			AC 500 V
Construction size			NH4
Utilization category			gL/gG
Status indicator			single indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with slotted blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			NH4
Rated current		A	800
Rated voltage		V	500
Voltage type			AC
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/dd9b7025-0e58-46b4-b717-66ce5e12c2b8.pdf

© 02/2021 by Eaton Industries GmbH