DC 3-wire Inductive Global Sensors
Tubular housing, M8×1



	M8 × 1	**M8 × 1**	**M8 × 1**	**M8 × 1**	**M8 × 1**
	Flush	Flush	Flush	Flush	Flush
	1.5 mm	**1.5 mm**	**1.5 mm**	**2 mm**	**2 mm**
	0...1.2 mm	0...1.2 mm	0...1.2 mm	0...1.6 mm	0...1.6 mm
	1X	1X	1X	2X	2X
	BES0027	**BES00CU**	**BES0037**	**BES00CK**	**BES00FC**
	BES M08MH1-PSC15B-S04G	BES M08EF-PSC15B-BP02-003	BES M08MI-PSC15B-BV02	BES M08EE-PSC20B-S49G-003	BES M08EE-PSC20B-S04G-003
	BES0026	**BES00CR**	**BES0030**	**BES00CF**	**BES00CE**
	BES M08MH1-POC15B-S04G	BES M08EF-POC15B-BP02-003	BES M08MI-POC15B-BV02	BES M08EE-POC20B-S49G-003	BES M08EE-POC20B-S04G-003
	BES0024	**BES00CN**	**BES002F**	**BES00C9**	**BES00C8**
	BES M08MH1-NSC15B-S04G	BES M08EF-NSC15B-BP02-003	BES M08MI-NSC15B-BV02	BES M08EE-NSC20B-S49G-003	BES M08EE-NSC20B-S04G-003
	BES0023	**BES00CL**	**BES03PJ**	**BES00C5**	**BES00C4**
	BES M08MH1-NOC15B-S04G	BES M08EF-NOC15B-BP02-003	BES M08MI-NOC15B-BV02	BES M08EE-NOC20B-S49G-003	BES M08EE-NOC20B-S04G-003
	12...30 V DC	10...30 V DC	12...30 V DC	10...30 V DC	10...30 V DC
	2 V	2.5 V	2 V	2.5 V	2.5 V
	75 V DC	250 V AC (⧈)	75 V DC	250 V AC (⧈)	250 V AC (⧈)
	200 mA	200 mA	200 mA	200 mA	200 mA
	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes
	–25...70 °C	–25...70 °C	–25...70 °C	–25...70 °C	–25...70 °C
	1 kHz	1 kHz	1 kHz	700 Hz	700 Hz
	Yellow LED	Yellow LED	Yellow LED	Yellow LED	Yellow LED
	IP 67	IP 67	IP 67	IP 67	IP 67
	CE, cULus	CE, cULus	CE, cULus	CE, cULus	CE, cULus
	Brass-coated	Stainless steel	Brass-coated	Stainless steel	Stainless steel
	PA 12	PBT	PA 12	PBT	PBT
	M12 connector, 4-pin	2 m PUR cable, 26 AWG	2 m PVC cable, 26 AWG	M8 connector, 3-pin	M12 connector, 4-pin
	BCC M415-0000-1A-003-VX44T2-020-C013			BCC M313-0000-10-001-VX43T2-020-C013	BCC M415-0000-1A-003-VX44T2-020-C013

