DATASHEET - SPBT12-280/3

Lightning current and surge arresters kit, TN-C kit, 3p

Part no.	**SPBT12-280/3**
	158330
EL Number (Norway)	**1609777**

General specifications	
Product name	Eaton Moeller series xPole - SPBT12 Surge protection device
Part no.	SPBT12-280/3
EAN	4015081548880
Product Length/Depth	86 millimetre
Product height	69 millimetre
Product width	52.5 millimetre
Product weight	0.429 kilogram
Compliances	RoHS conform
Product Tradename	xPole - SPBT12
Product Type	Surge protection device
Product Sub Type	None
Delivery program	
Application	Utility buildings Residential buildings Open areas
Number of poles	Three-pole
Type	Surge arrester
Technical Data - Electrical	
Voltage protection level	1.5 kV
Voltage protection level (DC+ - DC-)	0 kV
Voltage protection level (DC+/DC- - PE)	0 kV
Voltage protection level (L-N)	0 kV
Voltage protection level (L-PE)	1.5 kV
Voltage protection level (N-PE)	0 kV
Nominal voltage at AC	280 V
Nominal voltage at DC	0 V
Continuous voltage at AC - max	280 V
Continuous voltage at DC - max	0 V
PV-voltage - max	0 V
Lightning impulse current (10/350 µs)	12.5 kA
Follow current extinguishing capability	0 kA
Signalling at the device	Optic
Specific energy (W/R)	39.1 kJ/Ohm
Technical Data - Mechanical	
Frame	3 modular spacing
Mounting method	DIN rail (top hat rail) 35 mm
Conductor cross section (flexible, fine-strand) - max	35 mm^2
Conductor cross section (solid, solid-strand) - max	25 mm^2
Degree of protection	IP20
Additional information	
System configuration type	TT TN-S TN TN-C TN-C-S Other
Test class	Type 1 + 2

Technical data ETIM 9.0

Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457)			
Electric engineering, automation, process control engineering / Internal and external lightning protection / Combined SPD for energy and information technology / Energy and MSR technology (ecl@ss13-27-17-16-01 [AHE455002])			
System configuration DC			No
System configuration IT			No
System configuration TN			Yes
System configuration TN-C			Yes
System configuration TN-C-S			Yes
System configuration TN-S			Yes
System configuration TT			Yes
System configuration other			Yes
Number of poles			3
Lightning impulse current (10/350 µs)		kA	12.5
Max. continuous voltage AC		V	280
Max. continuous voltage DC		V	0
Nominal voltage AC		V	280
Nominal voltage DC		V	0
Max. PV-voltage		V	0
Voltage protection level		kV	1.5
Voltage protection level L-N		kV	0
Voltage protection level L-PE		kV	1.5
Voltage protection level N-PE		kV	0
Voltage protection level (DC+ - DC-)		kV	0
Voltage protection level (DC+/DC- - PE)		kV	0
Follow current extinguishing capability		kA	0
Specific energy (W/R)		kJ/Ohm	39.1
Max. overcurrent protection device, parallel connection (fuse)		A	0
Max. overcurrent protection device, series connection (fuse)		A	160
Mounting method			DIN rail (top hat rail) 35 mm
Construction size			3 modular spacing
Max. conductor cross section solid (solid, stranded)		mm^2	25
Max. conductor cross section flexible (fine-strand)		mm^2	35
Remote signalling			No
Signalling at the device			Optical
Test class			Type 1 + 2
Integrated backup fuse			No
Energy-coordinated protection effect with regard to the terminal equipment			No
Voltage switching spark gap technology			No
Overcurrent protected voltage tapping			No
Degree of protection (IP)			IP20

© 04/2023 by Eaton Industries GmbH