Ventilation







Description

Ventilation includes an extensive range of 4” and 6” extractor fans and accessories that are designed to seamlessly blend into the environment and are suitable for various applications, including kitchens, bathrooms and utility rooms.
Slim profile fans are designed to be highly energy efficient and quiet to meet ventilation requirements.
User adjustable timer and humidistat options providing an extra level of automation and effectiveness.
The new Zone One Axial and Flat Fascia fans offer even more efficient bathroom extraction due to their closer proximity to bath or shower trays

Features

- Sleek design
- Low energy fans – meet Building Regulation L1A specific fan power of less than 0.5W/l/s
- Low noise fans – meet Building Regulation F1 by being under 35dB @ 3m for less noise sensitive rooms
- Over run timers factory set at 15 minutes
- Humidistat factory set at 75% RH
- Ideal for through wall applications or with ducting lengths under 2m
- Fans have a one shot thermal fuse
- 3-year guarantee

Range

4” Zone 1 Timer	4700ZT
4” Zone 1 Timer & Humidistat	4700ZTH
4" Extractor Fan Pullcord Timer	4600P
4" Extractor Fan Pullcord Timer	4601P
6" Extractor Fan Pullcord	4660P
6" Extractor Fan Pullcord Timer	4661P
4” Zone 1 Flat Fascia Extractor Fan	4720Z
4” Zone 1 Flat Fascia Extractor Fan with Timer	4720ZT

Technical Specification

	4” Zone 1 Fan	4” Flat Fascia Fan	4” Extractor Fan	6” Extractor Fan
Extraction rate	24 l/s (88m³/hr)	23 l/s (83m³/hr)	24 l/s (87m³/hr)	63 l/s (227m/hr
Specific Fan Power	0.31W (l/s)	0.32W (l/s)	0.29W (l/s)	0.4W (l/s
Noise level	26dB@3m	29dB@3m	26dB@3m	35dB@3m
Voltage	240Vac	240Vac	240Vac	240Vac
Motor Rating	8W	8W	8W	18W
IP Rating	IP45	IP44	IP44	IP44
Ambient Temp	40°C Max.	40°C Max.	40°C Max.	40°C Max.
Insulation Class	Double Insulated	Double Insulated	Double Insulated	Double insulated
Over Run Timer	2-30mins. (4700ZT) (4700ZTH)	2-30mins. (4720ZT)	2-30mins. (4601P)	2-30mins. (4661P)
Humidistat	60-90% RH (4700ZTH)	N/A	N/A	N/A

No user serviceable parts

Dimensions (mm)

	4” Zone 1 Fan	4” Flat Fascia Fan	4” Extractor Fan	6” Extractor Fan
Height	136	160	150	205
Width	158	136	150	205
Recess Depth	81	79	79	99
Projection	26	38	19	22

Standards

BS EN 60335-2-80

Deta Electrical Company Ltd
UK: Panattoni Park Luton Road Chalton Bedfordshire LU4 9TT UK
EU: Unit 16 Ashbourne Industrial Estate Ashbourne Co. Meath A84 W972 Ireland
Tel. +44 1582 544 548 technical@deta.co.uk