DATASHEET - 10724687



Fuse-link, LV, 0.5 A, AC 690 V, 14 x 51 mm, aM, IEC

	C14M0.5
EL Number (Norway)	**1600205**

Similar to illustration

General specifications			
Product name			Eaton Bussmann series low voltage cylindrical fuse
Part no.			C14M0.5
EAN			5027590494229
Product Length/Depth			51 millimetre
Product height			14 millimetre
Product width			14 millimetre
Product weight			17.8 gram
Compliances			RoHS Compliant CE Marked
Certifications			IEC 60269
Product Tradename			None
Product Type			Low voltage cylindrical fuse
Product Sub Type			None
Electrical data			
Amperage Rating			0.5 A
Voltage rating			690 V
Voltage type			AC
Breaking capacity			120 kA
Utilization category			aM (switchgear protection)
Compatible fuse holder			
Suitable for			CH14 Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])

Model			Ceramic fuse
Size			14x51 mm
Voltage type			AC
Rated current		A	0.5
Rated voltage		V	690
Utilization category			aM (switchgear protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	120
Power loss at rated current		W	0.69

© 04/2023 by Eaton Industries GmbH