Specifications

# Eaton 135941



## Catalog Number: 135941

Eaton Moeller® series E57 Proximity switch, E57 Premium+ Series, 1 N/O, 3-wire, 6 - 48 V DC, M18 x 1 mm, Sn= 12 mm, Semi-shielded, PNP, Stainless steel, 2 m connection cable

### General specifications

**Product Name**
Eaton Moeller® series E57 Proximity switch

**Catalog Number**
135941

**EAN**
4015081327348

**Product Length/Depth**
127 mm

**Product Height**
154.94 mm

**Product Width**
48.26 mm

**Product Weight**
0.14 kg

**Certifications**
CSA File No.: none
None
CSA Class No.: none
IEC/EN 60947-5-2

Powering Business Worldwide

## Product specifications

### Type
Inductive sensor

### Electric connection type
Cable

### Enclosure material finishing
Other

### Actuation type
Metallic Target

### Enclosure material
Metal

### Enclosure type
Cylinder, screw-thread

### Category (EN 954-1)
B

### Explosion safety category for dust
None

### Explosion safety category for gas
None

### Safety performance level (EN ISO 13849-1)
None

### SIL (IEC 61508)
None

### Ambient operating temperature - max
70 °C

### Ambient operating temperature - min
-25 °C

### Diameter sensor
18 mm

### Number of contact energized outputs with signalling function
0

### Number of contacts (normally open contacts)
1

### Number of outputs (protected contact energized)
0

### Number of outputs (protected semiconductor)

## Resources

### Brochures
eaton-sensors-brochure-br053001en-en-us.pdf

### Catalogs
Product Range Catalog Sensors – products, basic information, applications

### Declarations of conformity
DA-DC-00004651.pdf

DA-DC-00004656.pdf

### Drawings
eaton-proximity-switches-e57-proximity-switch-dimensions-032.eps

eaton-proximity-switches-e57-proximity-switch-3d-drawing-003.eps

### eCAD model
DA-CE-ETN.E57-18LE12-B

### Installation instructions
IL05301003Z

### Multimedia
We make what matters

0

Number of outputs (semiconductor with signaling function)

1

Operational current (Ib) in the switched state at 24 V DC

10 A

Output current at protected output - max

0 mA

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Voltage type

DC

Mounting method

Semi-shielded mounting

Material

Stainless steel

Connection type

3-wire

2 m connection cable

Installation type

Concise

Degree of protection

IP67

NEMA 4X, 6, 13

Interface type

None

LED indicator

Status indication of Switching state: Red LED

Switch function type

Normally open contact

Load current

Max. 500 mA (Ie, at 6 - 30 V DC)

Residual current

0.1 mA (through the load in the blocked state at 230 V AC and 24 V DC)

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Switching frequency

800 Hz

Voltage rating - max

48 V

Width sensor

0 mm

Product category

E57 Premium+ Series

Switching output type

PNP

Temperature drift of sn

10 %

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

Rated control supply voltage (Us) at DC - max

48 V

Rated control supply voltage (Us) at DC - min

6 V

Rated switching distance (Sn) - max

12 mm

Repeatability

3 %

Sensor height

0 mm

Sensor length

66.1 mm

Supply voltage - max

48 V

Supply voltage - min

6 V

Switching hysteresis of Sn

15 %

Voltage drop (Ud)

2.5 V




Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia