DATASHEET - 400M450A 660V AC / 460V DC BS88 FUSE



Fuse-link, low voltage, 400 A, AC 660 V, DC 460 V, 80 kA, BS88/B4, 60 x 137 mm, gM, BS, motor-rated

Powering Business Worldwide

Part no. 400M450A 660V AC / 460V DC BS88 FUSE
Catalog No. TMF400M450

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	400
Motor current rating	I	A	400M450
Rated voltage			AC 660 V DC 460 V
Construction size			BS88/B4
Size			60 x 137 mm
Utilization category			gM
Description			motor-rated
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			centre-bolted tags
Standards/Regulations			BS88-2 IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])

Construction size			Other
Rated current		A	400
Rated voltage		V	660
Voltage type			AC/DC
Rated switching capacity		kA	80
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

© 02/2021 by Eaton Industries GmbH