Rittal – The System.

Faster – better – everywhere.

Interface flap, modular – SZ 2482.540

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Interface flap, modular – SZ 2482.540

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Design:	Interface inserts 2 x USB A (jack/jack)
Description:	For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.
Function principle:	The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required. All SUB-D interfaces may be rotated while in use
Material:	Mounting frame and metal flap: Fine die-cast zinc Plastic flap: Polycarbonate (semi-transparent) Lock: Polycarbonate
Surface finish:	Mounting frame and metal flap: Matt nickel-plated
Colour:	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)
Protection category IP to IEC 60 529:	IP 65 with sealed flap and proper assembly
Note on Model No.:	Conductively connected to mounting frame.

Product description

Design:	Note: Conductively connected to mounting frame.
Installation options:	In small and compact enclosures as a programming interface for controllers In IT and industrial distributors as maintenance access for networks

	In PC enclosures and console systems for the temporary connection of additional equipment in mobile Industrial Workstations for rapid connection to existing network structures In command panel systems for programming and maintenance of integral components.
Packs of:	1 pc(s).
Weight/pack:	0.08 kg
Copper weight (kg per piece):	0
EAN:	4028177490802
Customs tariff number:	85369095
ETIM 7.0:	EC002625
ETIM 6.0:	EC002625
eCl@ss 8.0/8.1:	27189234
eCl@ss 6.0/6.1:	27189234
Product description:	SZ Interface flap, modular, interface inserts, 2 x USB A, jack/jack

Approvals

Approvals:	C-UR UR + C-UR
Certificates:	NA