COMPLETE CONTROL STATIONS IP66

Type	Dimensions	Description	Head Colour	Text / Symbol	Contacts	Part Number
		Flush pushbutton Spring return	Green Red	⏽ ◎	1 x N/O 1 x N/C	LBX10110 LBX10610
		Mushroom head Ø40 Spring return	Red	◎	1 x N/C	LBX10210
		Selector switch 2 position stable	Grey / Black	◎ ⏽	1 x N/O	LBX12510
		Key switch 2 position stable Supplied With 2 Keys Profile 455 Removable Position 0 1	Grey / Black	◎ ⏽	1 x N/O	LBX12610
		Mushroom head Ø40 Turn to reset	Red	EMERGENCY STOP	1 x N/C	LBX10510
		EN418 Mushroom Head Ø40 Turn To Reset Yellow ring for head position visual indication Conforms to IEC 60947-5-5 / EN418	Red	EMERGENCY STOP	1 x N/C 2 x N/C	LBX17301 LBX17302
		EN418 Mushroom Head Ø40 Pull To Reset Yellow ring for head position visual indication Conforms to IEC 60947-5-5 / EN418	Red	EMERGENCY STOP	1 x N/C 2 x N/C	LBX15301 LBX15302
		EN418 Mushroom Head Ø40 Key To Reset Yellow ring for head position visual indication Conforms to IEC 60947-5-5 / EN418 Supplied With 2 Keys Profile 455	Red	EMERGENCY STOP	1 x N/C 2 x N/C	LBX11301 LBX11302
		EN418 Mushroom Head Ø54 Pull To Reset Flag & ring for head position visual indication Conforms to IEC 60947-5-5 / EN418	Red	STOP ⏽ STOP ⏽	1 x N/C 2 x N/C	LBX13101 LBX13102
		Flush pushbuttons x 2 Spring return	Green & Red	⏽ ◎	1 x N/O 1 x N/C	LBX20120

All enclosures conform to IEC 60947-5-1 and are rated to IP66
All contact blocks are mounted in the rear of the box
Front mounting contacts and other configurations are available please enquire for details