Date: 11/04/2023

TR33, 4...20mA, G1/2 fixed, 75 mm x 6 mm

TR33 Miniature resistance thermometer, thread-mounted

Item number:	48801949		
Quantity:	1 pcs.		
Order code:	TR33-Z-TT-CL2080-1360075-ZZZ-FZZ-ZZZ	R33	0086CW0000WIKA0Z
Overview:	TR33, 4...20mA, G1/2 fixed, 75 mm x 6 mm Output signal: 4...20mA -20°C 80 °C Electrical connection: Circular connector, M12x1 Process connection: Fixed threaded hex bushing G1/2 B Process temperature: -30 ... +150°C Sensor diameter ød: 6 mm Insertion length A: 75 mm Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F) Pin assignment: 1+ (10..30VDC) und 3- (0V) Specifications according to data sheet: TE 60.33		
Details:	TR33 Miniature resistance thermometer, thread-mounted Specifications according to data sheet: TE 60.33 Electrical connection: Circular connector, M12x1 Output signal: 4…20mA, 2-wire Transmitter Unit: °C Process temperature: -30 ... +150°C Transmitter initial value: -20°C Transmitter final value: 80 °C Process connection: Fixed threaded hex bushing G1/2 B Sensor diameter ød: 6 mm Insertion length A: 75 mm Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F) Pin assignment: Standard pin connection 1+ (10..30VDC) and 3- (0V)		

© 2023 - WIKA Instruments s.a.r.l.