DATASHEET - T0-3-8228/XZ

Reversing switches, T0, 20 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 5, 45 °, Design number 8228

Part no.	**T0-3-8228/XZ**
	013446
EL Number (Norway)	**1456678**

Product name			Eaton Moeller® series T0 Reversing switch
Part no.			T0-3-8228/XZ
EAN			4015080134466
Product Length/Depth			67 millimetre
Product height			48 millimetre
Product width			48 millimetre
Product weight			0.119 kilogram
Certifications			CE
Product Tradename			T0
Product Type			Reversing switch
Product Sub Type			None
Enclosure material			Plastic
Fitted with:			0 (off) position Retraction in 0-position
Number of poles			3
Degree of protection			IP65 NEMA 1 NEMA 12
Degree of protection (front side)			IP65 NEMA 12
Model			Reversing switch
Suitable for			Ground mounting Intermediate mounting
Type			Reversing switch
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V			11.5 A
Rated operational power at AC-3, 380/400 V, 50 Hz			4 kW
Rated operational power at AC-23A, 400 V, 50 Hz			5.5 kW
Rated operational voltage (Ue) at AC - max			690 V
Rated uninterrupted current (Iu)			20 A
Number of auxiliary contacts (change-over contacts)			0
Number of auxiliary contacts (normally closed contacts)			0
Number of auxiliary contacts (normally open contacts)			0
Actuator type			Short thumb-grip

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Off-load switch (EC001105)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Changeover switch (ecl@ss10.0.1-27-37-14-05 [AKF062013])

Model			Reversing switch
Number of poles			3
With zero (off) position			Yes
With retraction in 0-position			Yes
Rated permanent current Iu		A	20
Rated operation current Ie at AC-3, 400 V		A	11.5

Rated operation power at AC-3, 400 V		kW	4
Degree of protection (IP), front side			IP65
Degree of protection (NEMA), front side			12
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
Suitable for floor mounting			Yes
Suitable for front mounting			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			Yes
Complete device in housing			No
Material housing			Plastic
Type of control element			Short thumb-grip
Type of electrical connection of main circuit			Screw connection

© 04/2023 by Eaton Industries GmbH