Specifications

Eaton 107067



Catalog Number: 107067

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Busbar support, 3p, for flat busbars, NA

General specifications

Product Name
Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure

Catalog Number
107067

EAN
4015081069200

Product Length/Depth
50 mm

Product Height
190 mm

Product Width
20 mm

Product Weight
0.149 kg

Compliances
IEC 60439-1
UL508A
CE marking
CSA-C22.2 No. 14
UL CSA09 (refer to approbation report)
RoHS conform

Certifications
CSA (Class No. 3211-37)
CSA (File No. 236217)
Specially designed for North America
UL (File No. E300273)
North America (UL listed, CSA certified)
UL (Category Control Number NMTR, NMTR7)

Powering Business Worldwide

Product specifications

Used with

30 x 5/10 mm
12 x 5/10 mm
Feeder circuits
20 x 5/10 mm
System for flat busbar
60 mm system

Special features

Can be fitted to all busbar sizes using concertina system
With screw block inside

Type

60 mm system
System for flat busbar

Features

Halogen free
Self-extinguishing acc. UL 94

Creepage resistance

CTI 200

Current rating - max

630 A

Voltage rating (UL CSA 13)

Max. 600 V AC

Ambient operating temperature - max

35 °C

Busbar distance

60 mm

Number of poles

Three-pole

Degree of protection

Feeder circuits

Color

Light gray (RAL 7035)

Functions

Busbar support
UL busbar support

Resources

Brochures

eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf

Catalogs

eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

Product Range Catalog Switching and protecting motors

Certification reports

eaton-xeffect-sasy-60i-declaration-of-conformity.pdf

Characteristic curve

eaton-control-panels-characteristic-curve-002.eps

Drawings

eaton-control-panels-dimensions.eps

4300DRW-18

Installation instructions

IL015101ZU

Current limiting circuit breaker, refer to approbation report

Temperature resistance

Up to 120 °C

Rated operation current (Ie)

630 A

Suitable for

Three-pole

Material

Thermoplast, silicon free, chlorine free

Halogen free

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia