Date: 24/04/2023

733.51.100 2 bar 2 x G 1/2 B

Differential pressure gauge

Item number: 48605883

Quantity: 1 pcs.

Order code: 733.51-ZZZE-8BG320Z-AB-UZZZZASZZ-ZZZZZ 27A 3IHG3DIHZ-IZZZZZZ11ZZZ

Overview:
733.51.100 2 bar 2 x G 1/2 B
Connector location: lower mount
case: with pressure blowout disk
max. static pressure: 25 bar
Overpressure safety: 25 bar
class 1.6
Ingress protection: IP 65
Case filling fluid: glycerine-water-mixture
Window: laminated safety glass
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Pressure Gauge Standard: International (standard Europe)
WIKA Serial number *...*

Details:
Differential pressure gauge
Process industry series
All wellded construction
Model: 733.51
Specifications according to data sheet: PM 07.05
Case: stainless steel
Bezel ring: stainless steel
Movement: stainless steel
Case filling: with
Nominal size: 100 mm
Scale range: 0...2 bar
Process connection: 2 x G 1/2 B
Connector location: lower mount
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Accuracy class: class 1.6
max. static pressure: 25 bar
Overpressure safety: 25 bar
Case filling fluid: glycerine-water-mixture
Case material: Stainless steel 1.4301
Case surface: bare
Ingress protection: IP 65
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*

© 2023 - WIKA Instruments s.a.r.l.

serial number on dial: Serial number *...*
Window: laminated safety glass
case: with pressure blowout disk

© 2023 - WIKA Instruments s.a.r.l.