PILZ
THE SPIRIT OF SAFETY

PIT esc1 safe contact block 1 n/c 400315



PITestop, contact block, 1 N/C with monitoring, terminal (screw type).

Technical details

General data	
Approval:	CE, TÜV, EAC (Eurasian)
Self-monitored:	yes
Technical data	
Electrical data	
Min. contact current:	1 mA
Emergency stop	
Switch cap. E-STOP to standard:	EN 60947-5-1
Contact material E-STOP:	AgNi
Relay outputs	
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	250 V
Max. current AC15 safety cont.:	3 A
Voltage DC13 safety cont.:	24 V
Contact material:	AgNi
Environmental data	
Ambient temperature:	-30 - 70 °C
Pollution degree clear.&creep.:	3
Mechanical data	
Mounting position:	any

Connection terminal:	Screw terminal
Height dimension:	43 mm
Width dimension:	36 mm
Depth dimension:	7 mm
Net weight:	24 g
Gross weight:	26 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACh compliance:	Contains no SVHC substances
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85365080
UNSPSC 25:	39122216
EAN-Code:	4046548043617
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371302
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC000041
Volume:	0.027 dm3