UCPT1080

Wall mounted, 1035x835x300

The polyester single door compact wall mounted enclosure range, UCP/UCPT, with a IP 66 protection degree, is available off the shelf in many different sizes. Either a plain door or transparent door can be ordered. This enclosure range is well suited for outdoor installations, even when exposed to direct sunlight. The risk for component failure, and with that unnecessary downtime, is eliminated as water and dust are prevented from entering the enclosure.

Feature:
IP 66 TYPE 4, 4X, 12, 13 IK 08 / 07

CE UKCA GOST cULus_UL Listed



CHARACTERISTICS

Note	Transparent door
Height	1035 mm
Width	835 mm
Depth	300 mm
N° of locking points	3
Weight (kg)	22.25

Item no.: UCPT1080
EAN no.: 8713574100077

Technical data

Material: Fibre-glass reinforced polyester. UCPT viewing area: polycarbonate.

Body: Monoblock moulded 3 mm thick. Four holes for direct wall fixing. Without gland plate openings.

Door: Door, with or without window and 180° opening. For UCP/UCPT750 and above, a door support is supplied for easier closing. Sealing is by an injected one piece polyurethane gasket.

Lock: Double-bit 3 mm insert and 90° movement. UCP/UCPT540 and above have three locking points. Other locks are available as an accessory.

Temperature resistance: -25 °C to 70 °C in continuous use (peak temperatures up to 130 °C).

Characteristics: Self extinguishing and halogen free. Double insulated, according to EN61439-1. Rated insulation voltage Ui=1000V.

Protection: IP 66 | TYPE 4, 4X, 12, 13 and IP 65 only for UCPT430. Impact resistance IK 08 (IK 07 for enclosures with transparent door).

Approvals: CE, GOST. CSA and cULus_UL Listed approvals apply to plain door enclosures only. For further approvals, please contact nVent HOFFMAN's sales department.

Finish: RAL 7035, precoloured raw material.

Delivery: Enclosure with door, fixing screws for the mounting plate and a self adhesive rain strip.

Note: UCP320, UCP430 and UCP540 are delivered with the doors inside the packaging, unmounted.

Features

Feature:	Polyester single door wall mounted compact enclosures, mounted with either a plain or transparent door, with a high IP 66 protection degree.
Advantage:	Customers can choose enclosures that meet their requirements, off the shelf. The enclosure offers high corrosion resistance while being UV resistant. The installed components inside the enclosure will be safe and secure due to the high protection degree.
Benefit:	Customers can receive enclosures with a short delivery time, that match their requirements. The enclosure provides customers with an outdoor solution which can be exposed to direct sunlight, at a competitive price. Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the enclosure.