


ARCALUB-X.CHAIN-PINION-16B2-Z8-G

Chain lubrication pinion

Chain lubrication pinion duplex, Lubricant feed axial

Technical information



Your current product variant

Version	AB-/B-2	Chain lubrication pinions, duplex design

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website

Technical data

	Lubrication of chains	Usage
	Duplex (double-row)	Design
	axial	Lubricant feed
	Pinion: plastic, roller: open cell PU foam	Material
t_{op}	0 °C … +60 °C	Operating temperature
	7 m/s	Max. permissible circumferential speed at outside diameter
	Oil	Lubricant
	16 B-2	Chain type according to ISO 606
z	8	Teeth number
d	66.37 mm	Pitch circle diameter
d_a	75 mm	
d_b	48 mm	
B_1	40 mm	
B_2	10 mm	
B_3	30 mm	
L_1	30 mm	
L_2	40.5 mm	
L_3	40 mm	
L_4	81.2 mm	
G_1	M16	Thread
G_2	M10x1	Thread
W	15 mm	Width across flats
≈m	0.5 kg	Weight

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website