Specifications

Eaton 284832

Catalog Number: 284832

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Pushbutton actuator I and indicator light flush, pushbutton actuator 0 non-flush, momentary, White lens, white, black, inscribed, Bezel: titanium



General specifications

Product Name
Eaton Moeller® series M22 Double actuator pushbutton

Catalog Number
284832

EAN
4015082848323

Product Length/Depth
30 mm

Product Height
55 mm

Product Width
30 mm

Product Weight
0.015 kg

Compliances
Bureau Veritas
GoST-R
CE Marked

Certifications
CCC Marked
CSA Certified
Lloyd's Register Certified
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
IEC/EN 60947
IEC/EN 60947-5
CE
UL 508
VDE 0660
DNV
GL
LR

Includes contact block mounting adapter.

Powering Business Worldwide

Catalog Notes

Features & Functions

Bezel color
Titanium

Bezel material
Plastic

Design
Pushbutton actuator I and indicator light flush, pushbutton actuator 0 non-flush
Classical

Features
Labelled

Fitted with:
Front ring

Illumination
Illuminated

Inscription
Top I, Bottom O

Lens color
White

General

Degree of protection
NEMA 13
NEMA 3R
NEMA 12
IP66
NEMA 4X

Degree of protection (front side)
NEMA 4X
IP66

Lifespan, mechanical
200,000 Operations

Opening diameter
22.5 mm

Operating frequency
3600 Operations/h

Product category
RMQ-Titan

Size
Front dimensions: 29,7 x 54,7 mm

Suitable for
Illumination

Type
Double actuator

Ambient conditions, mechanical

Mounting position
As required

Shock resistance
Mechanical, According to IEC/EN 60068-2-27
30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Climatic environmental conditions

Ambient operating temperature - min
-25 °C

Ambient operating temperature - max
70 °C

Ambient storage temperature - min
40 °C

Ambient storage temperature - max
80 °C

Climatic proofing
Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Actuator

Actuating force

5 N

Actuator color

Black and white

Actuator function

Momentary

Spring-return

Communication

Connection to SmartWire-DT

With SWD-RMQ connections

Yes

Contacts

Force for positive opening - min

0 N

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Brochures

M22 Pilot Devices

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

Flip catalog - Product Range Catalog - Command and indication

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004157.pdf

DA-DC-00004135.pdf

Drawings

eaton-operating-pushbutton-m22-double-actuator-pushbutton-dimensions.eps

eaton-operating-pushbutton-m22-double-actuator-pushbutton-dimensions-002.eps

eaton-operating-button-m22-double-actuator-pushbutton-symbol-005.eps

eaton-general-approval-m22-symbol.eps

eaton-general-m22-symbol.eps

eaton-general-m22-standards.eps

eCAD model

ETN.284832.edz

Installation instructions

IL04716002Z

Installation videos

RMQ Flat Design

mCAD model

DA-CS-doppeldrucktaste_flach_normal

DA-CD-doppeldrucktaste_flach_normal

Multimedia

MCI Multicolor Light Indicator M22 with SmartWire-DT

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

RMQ small E-Stop emergency-stop button

MCI MultiColor Light Indicator RMQ compact solution

Sales notes

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

Specifications and datasheets

Eaton Specification Sheet - M22-DDLM-GR-X1-X0

System overview

Pilot devices - selection aid

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia