Specifications

Eaton 218402



Catalog Number: 218402

Eaton Moeller® series M22 Lens, indicator light white, flush, symbol klaxon

General specifications

Product Name
Eaton Moeller® series M22 Accessory Lens

Catalog Number
218402

EAN
4015082184025

Product Length/Depth
29 mm

Product Height
9 mm

Product Width
29 mm

Product Weight
0.002 kg

Certifications
UL/CSA certification not required

Powering Business Worldwide

Features & Functions

Design

Flush

Flat

Features

Labelled

Inscription

Individual inscription possible: ≤ 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm

Klaxon Symbol

Inscription type

Symbol

Lens color

White

General

Product category

Accessories

Type

Lenses for indicator lights

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Communication

Connection to SmartWire-DT

No

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal

Resources

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

Flip catalog - Product Range Catalog - Command and indication

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004157.pdf

DA-DC-00004135.pdf

Drawings

116C246

eCAD model

ETN.218402.edz

Installation instructions

IL04716002Z

Installation videos

RMQ Flat Design

mCAD model

DA-CS-linse_flach

elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

DA-CD-linse_flach

Multimedia

RMQ small E-Stop emergency-stop button

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

MCI Multicolor Light Indicator M22 with SmartWire-DT

MCI MultiColor Light Indicator RMQ compact solution

Sales notes

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

System overview

Pilot devices - selection aid

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia