700-751-ANT33



Cellular Antennas
with Magnetic base, 2dBi

- Gain 2 dBi
- 3 m Cable length
- SMA male connector
- Indoor

Info

REX industrial routers with an integrated cellular modem require an LTE antenna.For radio reception, a suitable antenna must be screwed to at least the SMA socket of the router "MAIN" (ANT 2).

Antenna wirh magnetic base. In order to improve the 4G data throughput, a second antenna terminal is available on the REX 100 LTE router with the SMA socket "Rx" (ANT1). If you would only like to install one antenna, we recommend the MiMo wall antenna, as it already contains two antennas in one housing.Our technical sales is happy to answer any questions you may have regarding the various antennas.

Technical data

General information	
Order number	700-751-ANT33
Article name	Magnetic base antenna, 2dBi, 3 m cable, SMA male connector
Scope of delivery	Magnetic base antenna, incl. cable
Transport and storage temperature	-40 °C ... +85 °C
Radio networks	LTE 800 | GSM 900 | GSM 1800, UMTS, LTE 2600
Frequency range	699–960 MHz | 1710–2690 MHz
Polarization	vertical
Gain	2.2 dBi
VSWR	<3.2 : 1
Max. input power	35 W
Impedance	50 Ω
Cable length	3 m, RG174
Connector type	SMA (m)
Magnetic base	31 mm
Height	70 mm