SLS.G - HEAT SHRINK WITH METAL RING IN THE SHAPE OF "D" - SLS | SLS.G32



Description

• Shrink tubing fitted with a strap and a shaped metal ring "D". This solution allows you to bring a point of attachment to all types of products and make them compatible with lanyards and carabiners Facom SLS. Examples: special tools, pen, spray, lever,
• The strap surrounds the shrink tubing for strength and maximum security for all.
• Fabric resistant to common solvents.
• Sheath equipped with an adhesive which becomes liquid with the heat during the retraction of the sheath. optimum temperature of withdrawal: between 150 and 300 ° depending on the thickness and diameter of the sheath.
• Excellent adhesion on most substrates: crude steel, chrome or phosphate, aluminum, wood, plastic, ...
Precautions:
- Clean and degrease the product that will receive the shrink tubing.
- Select the correct diameter of shrink-hose according to the allocation table.
- Identify a location where the sheath will not harm ergonomics. If possible, choose a location where the sheath can not escape once retracted.
- Respect the maximum weight recommended.
- Heat the sheath about 3 cm with a standard heat gun Facom E.2015. Be careful not to burn the strap.
- Cool 5 minutes to obtain optimum adhesion of the glue.
- Check the collage.
- Check the equipment periodically.

Information

d [mm]	40
H [mm]	50
[g]	40
[kg]	max,4,4

© FACOM 2017