SMB30FA	SMB30MM	SMB30Q	SMB30SC
			
All measurements in mm	All measurements in mm	All measurements in mm	All measurements in mm
A = 3/8 -16 x 50.8 **Hole size:** B = ø 30.1	**Hole center spacing:** A = 51.0, A to B = 25.4 **Hole size:** A = 42.6 x 7.0, B = ø 6.4, B = ø 30.1	**Hole center spacing:** A to B = 40.0 **Hole size:** A = ø 6.3, B = 13.1 x 6.3, A = ø 30.1	**Hole center spacing:** A to B = 50.8 **Hole size:** A = ø 7.0
• Swivel bracket with tilt and pan movement for precision adjustment • Mounting hole for 30 mm sensor • 12-ga. 304 stainless steel	• 12-ga. stainless steel bracket with curved mounting slots for versatility and orientation • Clearance for M6 (¼") hardware • Mounting hole for 30 mm sensor	• Right-angle flanged mounting bracket with curved slot for versatile orientation • 12-ga. stainless steel • Mounting hole for 30 mm sensor	• Swivel bracket with 30 mm mounting hole for sensor • Black reinforced thermoplastic polyester • Stainless steel mounting and swivel locking hardware included
Barrel Mount	**Barrel Mount**	**Barrel Mount**	**Barrel Mount**
			
Used with	Used with	Used with	Used with
QS30 SM30/SMI30 S30	T30 T30U EZ-LIGHT T30	QS30 S30 SM30/SMI30	EZ-LIGHT T30 T30	QS30 SM30/SMI30 S30	T30 EZ-LIGHT T30	QS30 SM30/SMI30 S30	T30 EZ-LIGHT T30
Base Mount	**Base Mount**	**Base Mount**	**Base Mount**
			
Used with	Used with	Used with	Used with
Q40 Q45 Q45U Q45UR QT50U OMNI-BEAM	OTB/LTB VTB STB K50 QT50R EZ-LIGHT K50L	Q40 Q45 OMNI-BEAM OTB/LTB VTB STB	QT50U Q45U Q45UR QT50R K50 EZ-LIGHT K50L	Q40 Q45 OMNI-BEAM OTB/LTB VTB STB	Q45U Q45UR K50 EZ-LIGHT K50L	Q40 Q45 OMNI-BEAM OTB/LTB VTB STB	QT50U Q45U Q45UR QT50R K50 EZ-LIGHT K50L