Date: 11/04/2023

MAGXXUN - 20...400 bar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F

Diaphragm pressure switch

Item number: 48763984

Quantity: 1 pcs.

Order code: MAGXXUN-BBVSC-2AMZZZZ1ZZZZZZZZZZZZZZZZZZZ ZCK5DW
B025000IZZZZZZZZ
F4-C5- - - - -

Overview:
MAGXXUN - 20...400 bar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F
Diaphragm pressure switch
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 1x SPDT silver contact
setting range: 20...400 bar
Standard, working range = 0...400 bar, proof pressure 600 bar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Hastelloy C 276//Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point customer-specifically configured
1. set point: 250.00 bar increasing,

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Diaphragm pressure switch
Flameproof enclosure Ex d
Model MA
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span
Contact version: 1x SPDT silver contact
setting range: 20...400 bar
working range: Standard, working range = 0...400 bar, proof pressure 600 bar
Set Point customer-specifically configured
Unit: bar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia

© 2023 - WIKA Instruments s.a.r.l.

Ingress Protection: IP66
MAGXXUN
Diaphragm: Hastelloy C 276//Connection: Stainless steel AISI 316L
1. set point: 250.00 bar increasing,

Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.