*Date: 23/01/2024*

# A-10 ; 0...600 bar gauge; 0 ... 10 V, 3-wire @ 14...30 V DC

## Pressure transmitter Model A-10

| | |
|---|---|
| Item number: | 12850781 |
| Quantity: | 1 pcs. |
| Order code: | A-10-6-BG560-HD1Z-FC-AGZ-ZW W1011A10Z-SZ3S-ZZFWPA-3AZZZSAZZZA3Z |
| Overview: | A-10 ; 0...600 bar gauge; 0 ... 10 V, 3-wire @ 14...30 V DC<br>Pressure transmitter Model A-10<br>Non-linearity: 0.5% BFSL<br>Process connection: G 1/4 A DIN EN ISO 1179-2; Sealing: NBR<br>Electrical connection: valve connector, size A<br>Pin assignment: U+=1, U-=2, S+=3<br>Permissible medium temperature: 0...+80 °C<br>Approvals: cULus<br>Type of packaging: folding box single<br>WIKA standard - specification according to data sheet PE 81.60 |
| Details: | Pressure transmitter Model A-10<br>for general applications<br>Specifications according to data sheet: PE 81.60<br>Wetted parts: 316L<br>Case: 316L<br>Non-linearity: 0.5% BFSL<br>Unit: bar<br>Pressure type: gauge<br>Measuring range: 0...600 bar gauge<br>Process connection: G 1/4 A DIN EN ISO 1179-2<br>Sealing: NBR<br>Permissible medium temperature: 0...+80 °C<br>Output signal: 0 ... 10 V, 3-wire<br>Power supply: 14...30 V DC<br>Electrical connection: valve connector, size A<br>Approvals: cULus<br>W1 (Wika standard)<br>Customer address: www.wika.com<br>Model name customer-specific: A-10<br>Pressure port: Standard<br>Type of packaging: folding box single<br>Sealing colour: WIKA standard (blue)<br>Test protocol: with test protocol<br>Main Language: English<br>Pin assignment: U+=1, U-=2, S+=3<br>Customer-specific: WIKA standard - specification according to data sheet<br>Model: A-10 2.0 |

*© 2024 - WIKA Instruments s.a.r.l.*

*Date: 23/01/2024*

Operating Instructions: with printed OI
Additional Data: without

*© 2024 - WIKA Instruments s.a.r.l.*