LD3 SLIM LED TRI-PROOF

LD3WPF363

36 W - 4300lm - 4000K



DIMENSIONS	A	B	C
1	66	68	1200



GENERAL INFORMATIONS	
Code	LD3WPF363
Ean	8031453026462
Family	LD3 SLIM LED TRI-PROOF
Technology	LED
Body material	ABS
Diffuser / lens material	PC
Operating temperature (° C)	-20 - +40
Years warranty	5
External driver	NO
Replaceable source	NO

LIGHTING DATA	
Light colour	CW
CCT (K)	4000
Luminous)ux (lm)	4300
Luminous Flux Module (lm)	5000
Beam (°)	120
Luminous Efflcacy (lm/W)	120
Color rendering (CRI)	>80

TECHNICAL FEATURES	
Power (W)	36
Supply voltage (V) / Max (V)	220 / 240
Power frequency (Hz)	50/60
Current consumption (mA)	156
Insulation class	2
Power factor	>0,90
Dimmer compatibility	NO
Nominal life (h)	50000
Impact resistance (IK)	8

PACKAGING	
Packaging	SL
Pack	12 / 12
Gross weight (Kg)	12.1
Net weight (Kg)	0.92

Bot Lighting srl con unico socio
Via Lombardia, 37/39 – 30030 Cazzago di Pianiga (VE) Italy - T. +39.041.51.29.411 – F. +39.041.51.01.715
www.botlighting.it – ordini@botlighting.it – info@botlighting.it
NOTE: dati soggetti a modifiche senza preavviso | NOTE: data subject to change without notice

Release 4/11/2024

LD3 SLIM LED TRI-PROOF

LD3WPF363
36W - 4300lm - 4000K

- Sealed tri-proof in polycarbonate
- Slim design
- High efficiency up to 140 lm/W
- Resistant to water, dust and corrosion

Bot Lighting srl con unico socio
Via Lombardia, 37/39 – 30030 Cazzago di Pianiga (VE) Italy - T. +39.041.51.29.411 – F. +39.041.51.01.715
www.botlighting.it – ordini@botlighting.it – info@botlighting.it
NOTE: dati soggetti a modifiche senza preavviso | NOTE: data subject to change without notice

Release 4/11/2024